



316-83-113-41-012101 Information

wviw.heisener.com

For Reference Only

Part Number 316-83-113-41-012101

Manufacturer Preci-Dip

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description PCB CONN SOLDER TAIL 2.54MM

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









316-83-113-41-012101 Specifications

Manufacturer Part Number 316-83-113-41-012101 Manufacturer Preci-Dip Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series 316 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5μin (0.75μm) Insulation Color Black Insulation Height 0.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)		
Category Connectors, Interconnects Package - Series 316 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)	Manufacturer Part Number	316-83-113-41-012101
Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series 316 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post 0.126" (3.20mm)	Manufacturer	Preci-Dip
Package - Series 316 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)	Category	Connectors, Interconnects
Series 316 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)	Package	-
Contact Type Female Socket Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)	Series	316
StyleBoard to BoardNumber of Positions13Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.354" (9.00mm)Contact Length - Post0.126" (3.20mm)	Connector Type	Socket
Number of Positions Number of Positions Loaded Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)	Contact Type	Female Socket
Number of Positions Loaded Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.354" (9.00mm)Contact Length - Post0.126" (3.20mm)	Number of Positions	13
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.354" (9.00mm)Contact Length - Post0.126" (3.20mm)	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.354" (9.00mm)Contact Length - Post0.126" (3.20mm)	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.354" (9.00mm)Contact Length - Post0.126" (3.20mm)	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5μin (0.75μm) Insulation Color Black Insulation Height 0.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)	Row Spacing - Mating	-
Fastening Type Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.354" (9.00mm) Contact Length - Post O.126" (3.20mm)	Mounting Type	Through Hole
Contact Finish - Mating Contact Finish Thickness - Mating 29.5μin (0.75μm) Insulation Color Black Insulation Height 0.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)	Termination	Solder
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)	Fastening Type	Push-Pull
Insulation Color Insulation Height O.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)	Contact Finish - Mating	Gold
Insulation Height 0.354" (9.00mm) Contact Length - Post 0.126" (3.20mm)	Contact Finish Thickness - Mating	29.5μin (0.75μm)
Contact Length - Post 0.126" (3.20mm)	Insulation Color	Black
-	Insulation Height	0.354" (9.00mm)
2000 4200	Contact Length - Post	0.126" (3.20mm)
Operating Temperature -55°C ~ 125°C	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

316-83-113-41-012101 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

316-83-113-41-012101 Payment Methods



















316-83-113-41-012101 Shipping Methods













If you have any question about 316-83-113-41-012101, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com