



317-83-113-41-026101 Information

www.neisener.lom

For Reference Only

Part Number 317-83-113-41-026101

Manufacturer Preci-Dip

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description PCB CONN SOLDER TAIL

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









317-83-113-41-026101 Specifications

Manufacturer Part Number317-83-113-41-026101ManufacturerPreci-DipCategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series317Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions13Number of Positions LoadedAllPitch - Mating0.070" (1.78mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5µin (0.75µm)Insulation ColorBlack		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series 317 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black	Manufacturer Part Number	317-83-113-41-026101
Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series 317 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black	Manufacturer	Preci-Dip
Package-Series317Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions13Number of Positions LoadedAllPitch - Mating0.070" (1.78mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5µin (0.75µm)Insulation ColorBlack	Category	Connectors, Interconnects
Series 317 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions13Number of Positions LoadedAllPitch - Mating0.070" (1.78mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlack	Series	317
StyleBoard to BoardNumber of Positions13Number of Positions LoadedAllPitch - Mating0.070" (1.78mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlack	Connector Type	Socket
Number of Positions13Number of Positions LoadedAllPitch - Mating0.070" (1.78mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlack	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.070" (1.78mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlack	Style	Board to Board
Pitch - Mating0.070" (1.78mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlack	Number of Positions	13
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlack	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlack	Pitch - Mating	0.070" (1.78mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlack	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5μin (0.75μm) Insulation Color Black	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating 29.5μin (0.75μm) Insulation Color Black	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlack	Termination	Solder
Contact Finish Thickness - Mating 29.5μin (0.75μm) Insulation Color Black	Fastening Type	Push-Pull
Insulation Color Black	Contact Finish - Mating	Gold
	Contact Finish Thickness - Mating	29.5μin (0.75μm)
0.2048 (10.00	Insulation Color	Black
Insulation Height 0.394" (10.00mm)	Insulation Height	0.394" (10.00mm)
Contact Length - Post 0.157" (4.00mm)	Contact Length - Post	0.157" (4.00mm)
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

317-83-113-41-026101 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

317-83-113-41-026101 Payment Methods



















317-83-113-41-026101 Shipping Methods













If you have any question about 317-83-113-41-026101, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com