

317-87-124-41-005101 Information



For Reference Only

Part Number 317-87-124-41-005101

Manufacturer Preci-Dip

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description PCB CONN SOLDER TAIL

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









317-87-124-41-005101 Specifications

Manufacturer Part Number 317-87-124-41-005101 Manufacturer Preci-Dip Category Connectors, Interconnects Package - Series 317 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series 317 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Manufacturer Part Number	317-87-124-41-005101
Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series 317 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Manufacturer	Preci-Dip
Package - Series 317 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Category	Connectors, Interconnects
Series 317 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Package	-
Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Series	317
Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Connector Type	Socket
Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.070" (1.78mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.070" (1.78mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlash	Style	Board to Board
Pitch - Mating0.070" (1.78mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlash	Number of Positions	24
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlash	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlash	Pitch - Mating	0.070" (1.78mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlash	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Mounting Type	Through Hole
Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Termination	Solder
Contact Finish Thickness - Mating Flash	Fastening Type	Push-Pull
•	Contact Finish - Mating	Gold
Insulation Color Black	Contact Finish Thickness - Mating	Flash
	Insulation Color	Black
Insulation Height 0.165" (4.20mm)	Insulation Height	0.165" (4.20mm)
Contact Length - Post 0.125" (3.18mm)	Contact Length - Post	0.125" (3.18mm)
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

317-87-124-41-005101 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

317-87-124-41-005101 Payment Methods



















317-87-124-41-005101 Shipping Methods













If you have any question about 317-87-124-41-005101, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com