

3182-2PG-515 Information



For Reference Only

Part Number 3182-2PG-515

Manufacturer Conxall/Switchcraft

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 2POS INLINE PIN

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3182-2PG-515 Specifications

Manufacturer Part Number3182-2PG-515ManufacturerConxall/SwitchcraftCategoryConnectors, InterconnectsPackage-SeriesMulti-Con-X?Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMulti-Con-X?Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Manufacturer Part Number	3182-2PG-515
PackageCircular ConnectorsSeriesMulti-Con-X?Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Manufacturer	Conxall/Switchcraft
Package-SeriesMulti-Con-X?Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Category	Connectors, Interconnects
SeriesMulti-Con-X?Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Package	-
Number of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Series	Multi-Con-X?
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated Current Rating -	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Number of Positions	2
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Shell Size - Insert	-
Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Shell Size, MIL	-
Fastening Type Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Termination	Solder Cup
Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Fastening Type	Bayonet Lock
Shell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Orientation	Keyed
Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Ingress Protection	Weathertight
Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Shell Material, Finish	Nylon
Voltage - Rated 600V Current Rating -	Contact Finish	Gold
Current Rating -	Features	Backshell, Cable Clamp
	Voltage - Rated	600V
Report errors?	Current Rating	-
		Report errors?

3182-2PG-515 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3182-2PG-515 Payment Methods



















3182-2PG-515 Shipping Methods













If you have any question about 3182-2PG-515, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com