



3186Y30I75999CJ Information

Heisener.com

Part Number 3186Y30I75999CJ

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY CONTACTOR 3PST 75A 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3186Y30I75999CJ Specifications

Manufacturer Part Number 3186Y30175999CJ Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series 3186, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 75A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)		
Category Relays Power Relays, Over 2 Amps Package - Series 3186, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 75A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	3186Y30I75999CJ
Package - Series 3186, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 75A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series 3186, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 75A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Category	Relays
Series3186, Products UnlimitedRelay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage24VACContact Form3PST-NO-DM (3 Form X)Contact Rating (Current)75ASwitching Voltage600VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)6 VACOperate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleBox Lug, Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage24VACContact Form3PST-NO-DM (3 Form X)Contact Rating (Current)75ASwitching Voltage600VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)6 VACOperate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleBox Lug, Quick Connect - 0.250" (6.3mm)	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage24VACContact Form3PST-NO-DM (3 Form X)Contact Rating (Current)75ASwitching Voltage600VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)6 VACOperate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleBox Lug, Quick Connect - 0.250" (6.3mm)	Series	3186, Products Unlimited
Coil Current Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 75A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Relay Type	Contactor
Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 75A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 75A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Coil Current	-
Contact Rating (Current) Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Coil Voltage	24VAC
Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Contact Form	3PST-NO-DM (3 Form X)
Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	75A
Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Switching Voltage	600VAC - Max
Operate Time - Release Time - Insulation - Class B Mounting Type Chassis Mount Box Lug, Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	18 VAC
Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	6 VAC
Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Operate Time	-
Mounting Type Chassis Mount Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Release Time	-
Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Box Lug, Quick Connect - 0.250" (6.3mm)
		Report errors?

3186Y30I75999CJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3186Y30I75999CJ Payment Methods



















3186Y30I75999CJ Shipping Methods













If you have any question about 3186Y30I75999CJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com