

31NT1-2 Information

Heisener.com

Part Number 31NT1-2

Manufacturer Honeywell Sensing and Productivity Solutions

Category Switches

Toggle Switches

Description SWITCH TOGGLE SPST 15A 125V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









31NT1-2 Specifications

Manufacturer Part Number Manufacturer Honeywell Sensing and Productivity Solutions Category Switches Toggle Switches Package - Series NT Circuit SPST Switch Function On-Off Current Rating 15A (AC) Voltage Rating - AC Voltage Rating - DC - Actuator Type Standard Round Actuator Length Illumination Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Direction Direction Part General Sealed Report errors?	M. C. D. W. I	213/771 2
Category Switches Toggle Switches Package - Series NT Circuit SPST Switch Function On-Off Current Rating 15A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Standard Round Actuator Length 17.02mm Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Bushing Thread 15/32-32 Ingress Protection Protection Series		
Toggle Switches Package - Series NT Circuit SPST Switch Function On-Off Current Rating 15A (AC) Voltage Rating - AC Voltage Rating - DC - Actuator Type Standard Round Actuator Length 17.02mm Illumination Illumination Type, Color - Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread Ingress Protection Package SPST SPST SPST SPST SPST SPST SPST SPS	Manufacturer	Honeywell Sensing and Productivity Solutions
Package - Series NT Circuit SPST Switch Function On-Off Current Rating 15A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Standard Round Actuator Length 17.02mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Sealed	Category	Switches
SeriesNTCircuitSPSTSwitch FunctionOn-OffCurrent Rating15A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeStandard RoundActuator Length17.02mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress ProtectionIP67/68 - Dust Tight, WaterproofFeaturesSealed		Toggle Switches
CircuitSPSTSwitch FunctionOn-OffCurrent Rating15A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeStandard RoundActuator Length17.02mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress ProtectionIP67/68 - Dust Tight, WaterproofFeaturesSealed	Package	-
Switch Function On-Off Current Rating 15A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Standard Round Actuator Length 17.02mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Screw Terminal	Series	NT
Current Rating15A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeStandard RoundActuator Length17.02mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress ProtectionIP67/68 - Dust Tight, WaterproofFeaturesSealed	Circuit	SPST
Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round 17.02mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features 125V Standard Round Non-Illumination Non-Illumination Non-Illuminated 17.02mm Non-Illuminated 17.02mm Non-Illuminated 17.02mm Non-Illuminated 17.02mm Sorew Terminal	Switch Function	On-Off
Voltage Rating - DC Actuator Type Standard Round Actuator Length 17.02mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Features Sealed	Current Rating	15A (AC)
Actuator Type Standard Round 17.02mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Scaled	Voltage Rating - AC	125V
Actuator Length 17.02mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Sealed	Voltage Rating - DC	-
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Sealed	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Sealed	Actuator Length	17.02mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Sealed	Illumination	Non-Illuminated
Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Sealed	Illumination Type, Color	-
Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Sealed	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Sealed	Mounting Type	Panel Mount
Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Sealed	Termination Style	Screw Terminal
Ingress Protection IP67/68 - Dust Tight, Waterproof Features Sealed	Panel Cutout Dimensions	Circular - 12.40mm Dia
Features Sealed	Bushing Thread	15/32-32
	Ingress Protection	IP67/68 - Dust Tight, Waterproof
Report errors?	Features	Sealed
Report errors.		Report errors?

31NT1-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

31NT1-2 Payment Methods





















31NT1-2 Shipping Methods













If you have any question about 31NT1-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com