

3209109 Information



For Reference Only

Part Number 3209109

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK ISOLATED 12-28 AWG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3209109 Specifications

Manufacturer Part Number 3209109 Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE STIO Type Isolated Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 10.4mm Termination Style Push In, Spring Current - IEC 18A Voltage - IEC 250V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE STIO Type Isolated Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 10.4mm Termination Style Push In, Spring Current - IEC 18A Voltage - IEC 250V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Manufacturer Part Number	3209109
Package - CLIPLINE STIO Type Isolated Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 10.4mm Termination Style Push In, Spring Current - IEC 18A Voltage - IEC 250V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Manufacturer	Phoenix Contact
Package - Series CLIPLINE STIO Type Isolated Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 10.4mm Termination Style Push In, Spring Current - IEC 18A Voltage - IEC 250V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Category	Connectors, Interconnects
Series CLIPLINE STIO Type Isolated Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 10.4mm Termination Style Push In, Spring Current - IEC 18A Voltage - IEC 250V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange		Terminal Blocks - Din Rail, Channel
Type Isolated Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 10.4mm Termination Style Push In, Spring Current - IEC 18A Voltage - IEC 250V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Package	-
Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 10.4mm Termination Style Push In, Spring Current - IEC 18A Voltage - IEC 250V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Series	CLIPLINE STIO
Number of Positions3Number of Levels1Terminal - Width10.4mmTermination StylePush In, SpringCurrent - IEC18AVoltage - IEC250VCurrent - UL10AVoltage - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-ColorOrange	Туре	Isolated
Number of Levels 1 Terminal - Width 10.4mm Termination Style Push In, Spring Current - IEC 18A Voltage - IEC 250V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 18A Voltage - IEC 250V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Orange	Number of Positions	3
Termination Style Current - IEC 18A Voltage - IEC 250V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Orange	Number of Levels	1
Current - IEC 18A Voltage - IEC 250V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Terminal - Width	10.4mm
Voltage - IEC Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Termination Style	Push In, Spring
Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Current - IEC	18A
Voltage - UL Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Voltage - IEC	250V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.08-4mm² Features Color Orange	Current - UL	10A
Wire Gauge or Range - mm² Features Color Orange	Voltage - UL	300V
Features - Color Orange	Wire Gauge or Range - AWG	12-28 AWG
Color Orange	Wire Gauge or Range - mm ²	0.08-4mm ²
	Features	-
	Color	Orange
Report errors?		Report errors?

3209109 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3209109 Payment Methods



















3209109 Shipping Methods













If you have any question about 3209109, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com