

3210033 Information



For Reference Only

Part Number 3210033

Manufacturer Phoenix Contact

Category Connectors, Interconnects Terminal Blocks - Specialized

Description TERM BLK PLUG 2POS 5.2MM GRAY

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3210033 Specifications

Manufacturer Part Number 3210033 Manufacturer Phoenix Contact Category Connectors, Interconnects Package - Series CLIPLINE PT Type Plug Connection Mounting Type DIN Rail Number of Positions 2 Number of Levels 1 Terminal - Width 5.2mm Termination Style Plug Receptacles, Push In, Spring Current - IEC 24A Voltage - IEC 500V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.14-4mm² Features - Housing Color Gray		
Category Connectors, Interconnects Terminal Blocks - Specialized Package - Series CLIPLINE PT Type Plug Connection Mounting Type DIN Rail Number of Positions 2 Number of Levels 1 Terminal - Width 5.2mm Termination Style Plug Receptacles, Push In, Spring Current - IEC 24A Voltage - IEC 500V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.14-4mm² Features - Housing Color Gray	Manufacturer Part Number	3210033
Package-SeriesCLIPLINE PTTypePlug ConnectionMounting TypeDIN RailNumber of Positions2Number of Levels1Terminal - Width5.2mmTermination StylePlug Receptacles, Push In, SpringCurrent - IEC24AVoltage - IEC500VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-4mm²Features-Housing ColorGray	Manufacturer	Phoenix Contact
Package-SeriesCLIPLINE PTTypePlug ConnectionMounting TypeDIN RailNumber of Positions2Number of Levels1Terminal - Width5.2mmTermination StylePlug Receptacles, Push In, SpringCurrent - IEC24AVoltage - IEC500VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-4mm²Features-Housing ColorGray	Category	Connectors, Interconnects
SeriesCLIPLINE PTTypePlug ConnectionMounting TypeDIN RailNumber of Positions2Number of Levels1Terminal - Width5.2mmTermination StylePlug Receptacles, Push In, SpringCurrent - IEC24AVoltage - IEC500VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-4mm²Features-Housing ColorGray		Terminal Blocks - Specialized
TypePlug ConnectionMounting TypeDIN RailNumber of Positions2Number of Levels1Terminal - Width5.2mmTermination StylePlug Receptacles, Push In, SpringCurrent - IEC24AVoltage - IEC500VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-4mm²Features-Housing ColorGray	Package	-
Mounting TypeDIN RailNumber of Positions2Number of Levels1Terminal - Width5.2mmTermination StylePlug Receptacles, Push In, SpringCurrent - IEC24AVoltage - IEC500VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-4mm²Features-Housing ColorGray	Series	CLIPLINE PT
Number of Positions 2 Number of Levels 1 Terminal - Width 5.2mm Termination Style Plug Receptacles, Push In, Spring Current - IEC 24A Voltage - IEC 500V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.14-4mm² Features Housing Color Gray	Туре	Plug Connection
Number of Levels1Terminal - Width5.2mmTermination StylePlug Receptacles, Push In, SpringCurrent - IEC24AVoltage - IEC500VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-4mm²Features-Housing ColorGray	Mounting Type	DIN Rail
Terminal - Width Termination Style Plug Receptacles, Push In, Spring Current - IEC 24A Voltage - IEC 500V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Housing Color 5.2mm 5.2mm 5.2mm 5.2mm 5.2mm 6.24A 24A 20A 20A 20A 20A 300V 6.12-26 AWG 0.14-4mm² Features - Housing Color Gray	Number of Positions	2
Termination Style Current - IEC 24A Voltage - IEC 500V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Housing Color Plug Receptacles, Push In, Spring 24A 24A 500V 500V 500V 20A 12-26 AWG 0.14-4mm² 6ray	Number of Levels	1
Current - IEC 24A Voltage - IEC 500V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.14-4mm² Features - Housing Color Gray	Terminal - Width	5.2mm
Voltage - IEC500VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-4mm²Features-Housing ColorGray	Termination Style	Plug Receptacles, Push In, Spring
Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.14-4mm² Features - Gray	Current - IEC	24A
Voltage - UL300VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-4mm²Features-Housing ColorGray	Voltage - IEC	500V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.14-4mm² Features Housing Color Gray	Current - UL	20A
Wire Gauge or Range - mm ² Features Housing Color Gray	Voltage - UL	300V
Features - Gray	Wire Gauge or Range - AWG	12-26 AWG
Housing Color Gray	Wire Gauge or Range - mm ²	0.14-4mm ²
	Features	-
Report errors?	Housing Color	Gray
report official.		Report errors?

3210033 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3210033 Payment Methods





















3210033 Shipping Methods













If you have any question about 3210033, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com