

### 3260118 Information



For Reference Only

**Part Number** 3260118

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

**Description** CONN TERM BLK FEED THRU 4/0-4AWG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 3260118 Specifications

| Manufacturer Part Number  Manufacturer  Phoenix Contact  Category  Connectors, Interconnects  Terminal Blocks - Din Rail, Channel  Package  Series  CLIPLINE PTPOWER  Type  Feed Through  Disconnect Type  Number of Positions  4  Number of Levels  2  Terminal - Width  125.0mm  Termination Style  Current - IEC  232A  Voltage - IEC  Lipu Syring  Voltage - UL  Wire Gauge or Range - AWG  |                                       |                                     |
|--|---------------------------------------|-------------------------------------|
| Category         Connectors, Interconnects           Terminal Blocks - Din Rail, Channel           Package         -           Series         CLIPLINE PTPOWER           Type         Feed Through           Disconnect Type         -           Number of Positions         4           Number of Levels         2           Terminal - Width         125.0mm           Termination Style         Push In, Spring           Current - IEC         232A           Voltage - IEC         1500V           Current - UL         230A           Voltage - UL         1000V           Wire Gauge or Range - AWG         4/0-4 AWG | Manufacturer Part Number              | 3260118                             |
| Terminal Blocks - Din Rail, Channel  | Manufacturer                          | Phoenix Contact                     |
| Package         -           Series         CLIPLINE PTPOWER           Type         Feed Through           Disconnect Type         -           Number of Positions         4           Number of Levels         2           Terminal - Width         125.0mm           Termination Style         Push In, Spring           Current - IEC         232A           Voltage - IEC         1500V           Current - UL         230A           Voltage - UL         1000V           Wire Gauge or Range - AWG         4/0-4 AWG  | Category                              | Connectors, Interconnects           |
| Series         CLIPLINE PTPOWER           Type         Feed Through           Disconnect Type         -           Number of Positions         4           Number of Levels         2           Terminal - Width         125.0mm           Termination Style         Push In, Spring           Current - IEC         232A           Voltage - IEC         1500V           Current - UL         230A           Voltage - UL         1000V           Wire Gauge or Range - AWG         4/0-4 AWG  |                                       | Terminal Blocks - Din Rail, Channel |
| Type Feed Through  Disconnect Type -  Number of Positions 4  Number of Levels 2  Terminal - Width 125.0mm  Termination Style Push In, Spring  Current - IEC 232A  Voltage - IEC 1500V  Current - UL 230A  Voltage - UL 1000V  Wire Gauge or Range - AWG 4/0-4 AWG  | Package                               | -                                   |
| Disconnect Type       -         Number of Positions       4         Number of Levels       2         Terminal - Width       125.0mm         Termination Style       Push In, Spring         Current - IEC       232A         Voltage - IEC       1500V         Current - UL       230A         Voltage - UL       1000V         Wire Gauge or Range - AWG       4/0-4 AWG  | Series                                | CLIPLINE PTPOWER                    |
| Number of Positions       4         Number of Levels       2         Terminal - Width       125.0mm         Termination Style       Push In, Spring         Current - IEC       232A         Voltage - IEC       1500V         Current - UL       230A         Voltage - UL       1000V         Wire Gauge or Range - AWG       4/0-4 AWG  | Туре                                  | Feed Through                        |
| Number of Levels       2         Terminal - Width       125.0mm         Termination Style       Push In, Spring         Current - IEC       232A         Voltage - IEC       1500V         Current - UL       230A         Voltage - UL       1000V         Wire Gauge or Range - AWG       4/0-4 AWG  | Disconnect Type                       | -                                   |
| Terminal - Width         125.0mm           Termination Style         Push In, Spring           Current - IEC         232A           Voltage - IEC         1500V           Current - UL         230A           Voltage - UL         1000V           Wire Gauge or Range - AWG         4/0-4 AWG   | Number of Positions                   | 4                                   |
| Termination Style         Push In, Spring           Current - IEC         232A           Voltage - IEC         1500V           Current - UL         230A           Voltage - UL         1000V           Wire Gauge or Range - AWG         4/0-4 AWG  | Number of Levels                      | 2                                   |
| Current - IEC       232A         Voltage - IEC       1500V         Current - UL       230A         Voltage - UL       1000V         Wire Gauge or Range - AWG       4/0-4 AWG  | Terminal - Width                      | 125.0mm                             |
| Voltage - IEC       1500V         Current - UL       230A         Voltage - UL       1000V         Wire Gauge or Range - AWG       4/0-4 AWG   | Termination Style                     | Push In, Spring                     |
| Current - UL 230A  Voltage - UL 1000V  Wire Gauge or Range - AWG 4/0-4 AWG   | Current - IEC                         | 232A                                |
| Voltage - UL 1000V Wire Gauge or Range - AWG 4/0-4 AWG   | Voltage - IEC                         | 1500V                               |
| Wire Gauge or Range - AWG 4/0-4 AWG  | Current - UL                          | 230A                                |
|  | Voltage - UL                          | 1000V                               |
| Wire Course or Bongs mm²   | Wire Gauge or Range - AWG             | 4/0-4 AWG                           |
| whe Gauge of Range - min-  | Wire Gauge or Range - mm <sup>2</sup> | 25-95mm <sup>2</sup>                |
| Features -   | Features                              | -                                   |
| Color Black, Blue, Gray, Yellow  | Color                                 | Black, Blue, Gray, Yellow           |
| Report errors?   |                                       | Report errors?                      |

#### 3260118 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 3260118 Payment Methods





















## 3260118 Shipping Methods













If you have any question about 3260118, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com