

3270302 Information



Part Number 3270302

Manufacturer Phoenix Contact

Category Connectors, Interconnects Terminal Blocks - Specialized

Description TERM BLK MARSHALLING 4POS 11.0MM

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3270302 Specifications

Manufacturer Part Number 3270302 Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Specialized Package - Series CLIPLINE PT Type Marshalling Connector Mounting Type Panel Mount Number of Positions 4 Number of Levels 1 Terminal - Width 11.0mm Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 500V Current - UL - Voltage - UL - Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.14-2.5mm² Features - Housing Color Gray		
CategoryConnectors, InterconnectsPackage-SeriesCLIPLINE PTTypeMarshalling ConnectorMounting TypePanel MountNumber of Positions4Number of Levels1Terminal - Width11.0mmTermination StylePush In, SpringCurrent - IEC17.5AVoltage - IEC500VCurrent - UL-Voltage - UL-Wire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-2.5mm²Features-Housing ColorGray	Manufacturer Part Number	3270302
Package - CLIPLINE PT Type Marshalling Connector Mounting Type Panel Mount Number of Positions 4 Number of Levels 1 Terminal - Width 11.0mm Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 500V Current - UL Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - AWG Housing Color Housing Color Gursel - Gray	Manufacturer	Phoenix Contact
Package-SeriesCLIPLINE PTTypeMarshalling ConnectorMounting TypePanel MountNumber of Positions4Number of Levels1Terminal - Width11.0mmTermination StylePush In, SpringCurrent - IEC17.5AVoltage - IEC500VCurrent - UL-Voltage - UL-Wire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-2.5mm²Features-Housing ColorGray	Category	Connectors, Interconnects
SeriesCLIPLINE PTTypeMarshalling ConnectorMounting TypePanel MountNumber of Positions4Number of Levels1Terminal - Width11.0mmTermination StylePush In, SpringCurrent - IEC17.5AVoltage - IEC500VCurrent - UL-Voltage - UL-Wire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-2.5mm²Features-Housing ColorGray		Terminal Blocks - Specialized
Type Marshalling Connector Mounting Type Panel Mount Number of Positions 4 Number of Levels 1 Terminal - Width 11.0mm Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 500V Current - UL - Voltage - UL - Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.14-2.5mm² Features - Housing Color Gray	Package	-
Mounting Type Panel Mount Number of Positions 4 Number of Levels 1 Terminal - Width 11.0mm Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 500V Current - UL - Voltage - UL - Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.14-2.5mm² Features - Housing Color Gray	Series	CLIPLINE PT
Number of Positions4Number of Levels1Terminal - Width11.0mmTermination StylePush In, SpringCurrent - IEC17.5AVoltage - IEC500VCurrent - UL-Voltage - UL-Wire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-2.5mm²Features-Housing ColorGray	Type	Marshalling Connector
Number of Levels Terminal - Width 11.0mm Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 500V Current - UL - Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Housing Color 11.0mm 11.0mm 12.26 AWG 12.26 AWG Gray	Mounting Type	Panel Mount
Terminal - Width Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 500V Current - UL - Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Housing Color 11.0mm 11.0mm 11.0mm 11.0mm 11.0mm 12.5A 17.5A 500V - 0.0V -	Number of Positions	4
Termination Style Current - IEC 17.5A Voltage - IEC 500V Current - UL - Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Housing Color Push In, Spring 17.5A 17.5A 500V - 0.14-2.5mm² Gray	Number of Levels	1
Current - IEC 17.5A Voltage - IEC 500V Current - UL - Voltage - UL - Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.14-2.5mm² Features - Housing Color Gray	Terminal - Width	11.0mm
Voltage - IEC500VCurrent - UL-Voltage - UL-Wire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.14-2.5mm²Features-Housing ColorGray	Termination Style	Push In, Spring
Current - UL Voltage - UL Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.14-2.5mm² Housing Color Gray	Current - IEC	17.5A
Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.14-2.5mm² Features - Housing Color Gray	Voltage - IEC	500V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.14-2.5mm² Features Housing Color Gray	Current - UL	-
Wire Gauge or Range - mm ² Features Housing Color O.14-2.5mm ² - Gray	Voltage - UL	-
Features - Housing Color Gray	Wire Gauge or Range - AWG	12-26 AWG
Housing Color Gray	Wire Gauge or Range - mm ²	0.14-2.5mm ²
	Features	-
Report errors?	Housing Color	Gray
		Report errors?

3270302 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3270302 Payment Methods



















3270302 Shipping Methods













If you have any question about 3270302, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com