

3280-6SG-530 Information

Heisener com

Part Number 3280-6SG-530

Manufacturer Connectors, Interconnects
Circular Connectors

Description CONN PLUG 6POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3280-6SG-530 Specifications

Manufacturer Part Number 3280-6SG-530 Manufacturer Conxall/Switchcraft Category Connectors, Interconnects Package - Series Multi-Con-X? Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMulti-Con-X?Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Manufacturer Part Number	3280-6SG-530
PackageCircular ConnectorsSeriesMulti-Con-X?Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Manufacturer	Conxall/Switchcraft
Package-SeriesMulti-Con-X?Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Category	Connectors, Interconnects
SeriesMulti-Con-X?Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Package	-
Number of Positions6Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Series	Multi-Con-X?
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Number of Positions	6
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Shell Size - Insert	-
Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Shell Size, MIL	-
Fastening Type Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Termination	Crimp
Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Fastening Type	Bayonet Lock
Shell Material, FinishNylonContact FinishGoldFeaturesBackshell, Cable ClampVoltage - Rated600VCurrent Rating-	Orientation	Keyed
Contact Finish Gold Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Ingress Protection	Weathertight
Features Backshell, Cable Clamp Voltage - Rated 600V Current Rating -	Shell Material, Finish	Nylon
Voltage - Rated 600V Current Rating -	Contact Finish	Gold
Current Rating -	Features	Backshell, Cable Clamp
-	Voltage - Rated	600V
Report errors?	Current Rating	-
		Report errors?

3280-6SG-530 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3280-6SG-530 Payment Methods





















3280-6SG-530 Shipping Methods













If you have any question about 3280-6SG-530, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com