

## 32NT391-7-C08 Information

Melsener.com

For Reference Only

**Part Number** 32NT391-7-C08

Manufacturer Honeywell Sensing and Productivity Solutions

**Category** Switches

Toggle Switches

**Description** SWITCH TOGGLE DPDT 10A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 32NT391-7-C08 Specifications

Manufacturer Category Switches Toggle Switches Package - Series NT Circuit DPDT Switch Function Mom-Off-Mom Current Rating 10A (AC) Voltage Rating - AC Voltage Rating - DC Actuator Type Flatted Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features Yellow Actuator Features Yellow Actuator Index Switches Inggle Switches	M. C. D. M. I	20NF201 7 C00
Category Switches Toggle Switches  Package - Series NT Circuit DPDT Switch Function Mom-Off-Mom Current Rating 10A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Flatted Actuator Length 122.35mm Illumination Non-Illuminated 1Illumination Type, Color - Illumination Type, Color - Illumination Type Panel Mount Termination Style Quick Connect - 0.250" (6.3mm) Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Yellow Actuator	Manufacturer Part Number	32NT391-7-C08
Package - Series NT Circuit DPDT Switch Function Mom-Off-Mom Current Rating 10A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Flatted Actuator Length 22.35mm Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Quick Connect - 0.250" (6.3mm) Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Pe6/68 - Dust Tight, Waterproof Features Yellow Actuator	Manufacturer	
Package - Series NT Circuit DPDT Switch Function Mom-Off-Mom Current Rating 10A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Flatted Actuator Length 22.35mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Quick Connect - 0.250" (6.3mm) Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features	Category	Switches
Series NT Circuit DPDT Switch Function Mom-Off-Mom Current Rating 10A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Flatted Actuator Length 22.35mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Quick Connect - 0.250" (6.3mm) Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features		Toggle Switches
Circuit DPDT  Switch Function Mom-Off-Mom  Current Rating 10A (AC)  Voltage Rating - AC 125V  Voltage Rating - DC - Actuator Type Flatted  Actuator Length 22.35mm  Illumination Non-Illuminated  Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount  Termination Style Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions Circular - 12.40mm Dia  Bushing Thread 15/32-32  Ingress Protection IP67/68 - Dust Tight, Waterproof  Features Yellow Actuator	Package	-
Switch Function Mom-Off-Mom Current Rating 10A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Flatted Actuator Length 22.35mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Quick Connect - 0.250" (6.3mm) Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Yellow Actuator	Series	NT
Current Rating 10A (AC)  Voltage Rating - AC 125V  Voltage Rating - DC - Actuator Type Flatted  Actuator Length 22.35mm  Illumination Non-Illuminated  Illumination Type, Color - Illumination Voltage (Nominal) -  Mounting Type Panel Mount  Termination Style Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions Circular - 12.40mm Dia  Bushing Thread 15/32-32  Ingress Protection IP67/68 - Dust Tight, Waterproof  Features Yellow Actuator	Circuit	DPDT
Voltage Rating - AC  Voltage Rating - DC  Actuator Type  Flatted  Actuator Length  Illumination  Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Mounting Type  Panel Mount  Termination Style  Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions  Circular - 12.40mm Dia  Bushing Thread  Ingress Protection  IP67/68 - Dust Tight, Waterproof  Features  Yellow Actuator	Switch Function	Mom-Off-Mom
Voltage Rating - DC  Actuator Type Flatted  Actuator Length 22.35mm  Illumination Non-Illuminated  Illumination Type, Color - Illumination Voltage (Nominal)  Mounting Type Panel Mount Termination Style Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions Circular - 12.40mm Dia  Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Yellow Actuator	Current Rating	10A (AC)
Actuator Type Actuator Length 22.35mm  Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Quick Connect - 0.250" (6.3mm) Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Yellow Actuator	Voltage Rating - AC	125V
Actuator Length 22.35mm  Illumination Non-Illuminated  Illumination Type, Color -  Illumination Voltage (Nominal) -  Mounting Type Panel Mount  Termination Style Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions Circular - 12.40mm Dia  Bushing Thread 15/32-32  Ingress Protection IP67/68 - Dust Tight, Waterproof  Features Yellow Actuator	Voltage Rating - DC	-
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Quick Connect - 0.250" (6.3mm) Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Yellow Actuator	Actuator Type	Flatted
Illumination Type, Color  Illumination Voltage (Nominal)  Mounting Type  Panel Mount  Termination Style  Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions  Circular - 12.40mm Dia  Bushing Thread  15/32-32  Ingress Protection  IP67/68 - Dust Tight, Waterproof  Features  Yellow Actuator	Actuator Length	22.35mm
Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions Circular - 12.40mm Dia  Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof  Features Yellow Actuator	Illumination	Non-Illuminated
Mounting Type Panel Mount  Termination Style Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions Circular - 12.40mm Dia  Bushing Thread 15/32-32  Ingress Protection IP67/68 - Dust Tight, Waterproof  Features Yellow Actuator	Illumination Type, Color	-
Termination Style Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions Circular - 12.40mm Dia  Bushing Thread 15/32-32  Ingress Protection IP67/68 - Dust Tight, Waterproof  Features Yellow Actuator	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions  Circular - 12.40mm Dia  Bushing Thread  15/32-32  Ingress Protection  IP67/68 - Dust Tight, Waterproof  Features  Yellow Actuator	Mounting Type	Panel Mount
Bushing Thread 15/32-32 Ingress Protection IP67/68 - Dust Tight, Waterproof Features Yellow Actuator	Termination Style	Quick Connect - 0.250" (6.3mm)
Ingress Protection IP67/68 - Dust Tight, Waterproof Features Yellow Actuator	Panel Cutout Dimensions	Circular - 12.40mm Dia
Features Yellow Actuator	Bushing Thread	15/32-32
	Ingress Protection	IP67/68 - Dust Tight, Waterproof
Deposit amount	Features	Yellow Actuator
Report errors?		Report errors?

#### 32NT391-7-C08 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 32NT391-7-C08 Payment Methods



















## 32NT391-7-C08 Shipping Methods













If you have any question about 32NT391-7-C08, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com