



### 335CKS400MJM Information



For Reference Only

Part Number 335CKS400MJM Manufacturer Illinois Capacitor

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 3.3UF 20% 400V T/H

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 335CKS400MJM Specifications

Manufacturer Part Number         335CKS400MJM           Manufacturer         Illinois Capacitors           Category         Capacitors           Package         Radial, Can           Series         CKS           Capacitance         3.3µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         100.477 Ohm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         55mA @ 120Hz           Ripple Current - High Frequency         137.5mA @ 100kHz           Impedance         -           Lead Spacing         0.138" (3.50mm)           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.512" (13.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         CKS           Capacitance         3.3µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         100.477 Ohm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         55mA @ 120Hz           Ripple Current - High Frequency         137.5mA @ 100kHz           Impedance         -           Lead Spacing         0.138" (3.50mm)           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.512" (13.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	335CKS400MJM
Package         Radial, Can           Series         CKS           Capacitance         3.3µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         100.477 Ohm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         55mA @ 120Hz           Ripple Current - High Frequency         137.5mA @ 100kHz           Impedance         -           Lead Spacing         0.138" (3.50mm)           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.512" (13.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	Illinois Capacitor
Package         Radial, Can           Series         CKS           Capacitance         3.3μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         100.477 Ohm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         55mA @ 120Hz           Ripple Current - High Frequency         137.5mA @ 100kHz           Impedance         -           Lead Spacing         0.138" (3.50mm)           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.512" (13.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         CKS           Capacitance         3.3μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         100.477 Ohm @ 120Hz           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         55mA @ 120Hz           Ripple Current - High Frequency         137.5mA @ 100kHz           Impedance         -           Lead Spacing         0.138" (3.50mm)           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.512" (13.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance       3.3µF         Tolerance       ±20%         Voltage - Rated       400V         ESR (Equivalent Series Resistance)       100.477 Ohm @ 120Hz         Lifetime @ Temp.       2000 Hrs @ 85°C         Operating Temperature       -25°C ~ 85°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       55mA @ 120Hz         Ripple Current - High Frequency       137.5mA @ 100kHz         Impedance       -         Lead Spacing       0.138" (3.50mm)         Size / Dimension       0.315" Dia (8.00mm)         Height - Seated (Max)       0.512" (13.00mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) 100.477 Ohm @ 120Hz  Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -25°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 55mA @ 120Hz  Ripple Current - High Frequency 137.5mA @ 100kHz  Impedance -  Lead Spacing 0.138" (3.50mm)  Size / Dimension 0.315" Dia (8.00mm)  Height - Seated (Max) 0.512" (13.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	CKS
Voltage - Rated 400V  ESR (Equivalent Series Resistance) 100.477 Ohm @ 120Hz  Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -25°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 55mA @ 120Hz  Ripple Current - High Frequency 137.5mA @ 100kHz  Impedance - Lead Spacing 0.138" (3.50mm)  Size / Dimension 0.315" Dia (8.00mm)  Height - Seated (Max) 0.512" (13.00mm)  Surface Mount Land Size  Mounting Type Through Hole Package / Case Radial, Can	Capacitance	3.3µF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  55mA @ 120Hz  Ripple Current - High Frequency  137.5mA @ 100kHz  Impedance  -  Lead Spacing  0.138" (3.50mm)  Size / Dimension  0.315" Dia (8.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  S5mA @ 120Hz  Ripple Current - High Frequency  137.5mA @ 100kHz  Impedance  - Lead Spacing  0.138" (3.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  2000 Hrs @ 85°C  -25°C ~ 85°C  Reneral Purpose  General Purpose  137.5mA @ 120Hz  137.5mA @ 120Hz  137.5mA @ 100kHz  -  137.5mA @ 100kHz  -	Voltage - Rated	400V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency S5mA @ 120Hz Ripple Current - High Frequency 137.5mA @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	100.477 Ohm @ 120Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 55mA @ 120Hz  Ripple Current - High Frequency 137.5mA @ 100kHz  Impedance -  Lead Spacing 0.138" (3.50mm)  Size / Dimension 0.315" Dia (8.00mm)  Height - Seated (Max) 0.512" (13.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications  General Purpose  Ripple Current - Low Frequency  S5mA @ 120Hz  Ripple Current - High Frequency  137.5mA @ 100kHz  Impedance  Lead Spacing  0.138" (3.50mm)  Size / Dimension  0.315" Dia (8.00mm)  Height - Seated (Max)  0.512" (13.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  137.5mA @ 100kHz  Impedance  - Lead Spacing  0.138" (3.50mm)  Size / Dimension  0.315" Dia (8.00mm)  Height - Seated (Max)  0.512" (13.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	55mA @ 120Hz
Lead Spacing 0.138" (3.50mm)  Size / Dimension 0.315" Dia (8.00mm)  Height - Seated (Max) 0.512" (13.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Ripple Current - High Frequency	137.5mA @ 100kHz
Size / Dimension 0.315" Dia (8.00mm)  Height - Seated (Max) 0.512" (13.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.315" Dia (8.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.512" (13.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### 335CKS400MJM Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 335CKS400MJM Payment Methods



















## 335CKS400MJM Shipping Methods













If you have any question about 335CKS400MJM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com