



335PSB102K2R Information



For Reference Only

Part Number 335PSB102K2R
Manufacturer Illinois Capacitor
Category Capacitors
Film Capacitors

Description CAP FILM 3.3UF 10% 1KVDC RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









335PSB102K2R Specifications

Manufacturer Part Number 335PSB102K2R Manufacturer Illinois Capacitors Category Capacitors Package Radial Series PSB Capacitance 3.3µF Tolerance ±10% Voltage Rating - AC 575V Voltage Rating - DC 1000V (1kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.8 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features - Report errors?	•		
Category Capacitors Film Capacitors Radial Series PSB Capacitance 3.3µF Tolerance ±10% Voltage Rating - AC Voltage Rating - DC Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature 40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Termination PC Pins Lead Spacing Applications Features Capacitors Fadial FSB Radial FSB Redial Film Capacitors Radial FSB Redial Film Capacitors Features Radial FSB Redial Film Capacitors Radial FILM Capacitors Features Capacitors Film Capacitors Follows Film Capacitors Follows Film Capacitors Fadial FSB Redial Film Capacitors Follows Film Capacitors Follows Film Capacitors Film Capacitors Film Capacitors Follows Film Capacitors Film Capacitors Follows Film Capacitors F	Manufacturer Part Number	335PSB102K2R	
Package Radial Series PSB Capacitance 3.3μF Tolerance ±10% Voltage Rating - AC 575V Voltage Rating - DC 1000V (1kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.8 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Manufacturer	Illinois Capacitor	
PackageRadialSeriesPSBCapacitance3.3μFTolerance±10%Voltage Rating - AC575VVoltage Ratirg - DC1000V (1kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)2.8 mOhmOperating Temperature-40°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Category	Capacitors	
Series PSB Capacitance 3.3µF Tolerance ±10% Voltage Rating - AC 575V Voltage Rating - DC 1000V (1kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.8 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -		Film Capacitors	
Capacitance $3.3 \mu F$ Tolerance $\pm 10\%$ Voltage Rating - AC 575V Voltage Rating - DC $1000 \text{V} (1 \text{kV})$ Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance) 2.8 mOhm Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Mounting TypeThrough HolePackage / CaseRadialSize / Dimension $2.264^{\circ}\text{L} \times 1.378^{\circ}\text{W} (57.50 \text{mm} \times 35.00 \text{mm})$ Height - Seated (Max) 1.969° (50.00 mm)TerminationPC PinsLead Spacing 2.067° (52.50 mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Package	Radial	
Tolerance ±10% Voltage Rating - AC 575V Voltage Rating - DC 1000V (1kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.8 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Series	PSB	
Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.8 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features	Capacitance	3.3µF	
Voltage Rating - DC Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.8 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Tolerance	±10%	
Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Voltage Rating - AC	575V	
ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension Leight - Seated (Max) Termination PC Pins Lead Spacing Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features - 2.8 mOhm -40°C ~ 100°C Through Hole Radial 2.264" L x 1.378" W (57.50mm x 35.00mm) 1.969" (50.00mm) PC Pins Lead Spacing Applications High Frequency, Switching; High Pulse, DV/DT; Snubber	Voltage Rating - DC	1000V (1kV)	
Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Dielectric Material	Polypropylene (PP), Metallized	
Mounting Type Package / Case Radial Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	ESR (Equivalent Series Resistance)	2.8 mOhm	
Package / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Operating Temperature	-40°C ~ 100°C	
Size / Dimension 2.264" L x 1.378" W (57.50mm x 35.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Mounting Type	Through Hole	
Height - Seated (Max) 1.969" (50.00mm) PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Package / Case	Radial	
Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Size / Dimension	2.264" L x 1.378" W (57.50mm x 35.00mm)	
Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Height - Seated (Max)	1.969" (50.00mm)	
Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Termination	PC Pins	
Features -	Lead Spacing	2.067" (52.50mm)	
	Applications	High Frequency, Switching; High Pulse, DV/DT; Snubber	
Report errors?	Features	-	
			Report errors?

335PSB102K2R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

335PSB102K2R Payment Methods



















335PSB102K2R Shipping Methods













If you have any question about 335PSB102K2R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com