

336AXZ010M

336AXZ010M Information



For Reference Only

Part Number	336AXZ010M	
Manufacturer	Illinois Capacitor	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP ALUM 33UF 20% 10V SMD	
Package	Radial, Can - SMD	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



336AXZ010M Specifications

Manufacturer Illinois Capacitor Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series AXZ Capacitance 33µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 10.05 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 75mA @ 120Hz Impedance 760 mOhms Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm)		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAXZCapacitance33µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)10.05 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 100kHzImpedance760 mOhmsLead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Manufacturer Part Number	336AXZ010M
Aluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAXZCapacitance33µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)10.05 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency150mA @ 100HzRipple Current - High Frequency-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Package / CaseRadial, Can - SMD	Manufacturer	Illinois Capacitor
PackageRadial, Can - SMDSeriesAXZCapacitance33µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)10.05 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency150mA @ 100HzImpedance-Size / Dimension0.197" Dia (5.00mm)Lead Spacing-Size / Dimension0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Package / CaseRadial, Can - SMD	Category	Capacitors
SeriesAXZCapacitance33µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)10.05 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzImpedance760 mOhmsLead Spacing.Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Package / CaseRadial, Can - SMD		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)10.05 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzInpedance760 mOhmsLead Spacing.Size / Dimension0.197° Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Package / CaseRadial, Can - SMD	Package	Radial, Can - SMD
Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 10.05 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 75mA @ 120Hz Impedance 760 mOhms Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Package / Case Radial, Can - SMD	Series	AXZ
Voltage - RatedIOVESR (Equivalent Series Resistance)10.05 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzImpedance-60 mOhmsLead Spacing-100 mOhmsSize / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land SizeSurface MountPackage / CaseRadial, Can - SMD	Capacitance	33µF
ESR (Equivalent Series Resistance)10.05 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzBipple Current - High Frequency150mA @ 100kHzImpedance-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land SizeSurface MountPackage / CaseRadial, Can - SMD	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarPolarizationsGeneral PurposeApplications75mA @ 120HzRipple Current - Low Frequency150mA @ 100kHzImpedance760 mOhmsLead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.209" L x 0.209" W (5.30mm x 5.30mm)Surface Mount Land SizeSurface MountPackage / CaseRadial, Can - SMD	Voltage - Rated	10V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 100kHzImpedance760 mOhmsLead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.209" L x 0.209" W (5.30mm x 5.30mm)Surface Mount Land SizeSurface MountPackage / CaseRadial, Can - SMD	ESR (Equivalent Series Resistance)	10.05 Ohm @ 120Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 100kHzImpedance760 mOhmsLead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Lifetime @ Temp.	2000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 100kHzImpedance760 mOhmsLead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency75mA @ 120HzRipple Current - High Frequency150mA @ 100kHzImpedance760 mOhmsLead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Polarization	Polar
Ripple Current - High Frequency150mA @ 100kHzImpedance760 mOhmsLead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Applications	General Purpose
Impedance760 mOhmsLead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - Low Frequency	75mA @ 120Hz
Lead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - High Frequency	150mA @ 100kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Impedance	760 mOhms
Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Lead Spacing	-
Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Size / Dimension	0.197" Dia (5.00mm)
Mounting Type Surface Mount Package / Case Radial, Can - SMD	Height - Seated (Max)	0.217" (5.50mm)
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.209" L x 0.209" W (5.30mm x 5.30mm)
-	Mounting Type	Surface Mount
Report errors?	Package / Case	Radial, Can - SMD
		Report errors?

336AXZ010M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

336AXZ010M Payment Methods





If you have any question about 336AXZ010M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com