

3403.0165.11

3403.0165.11 Information



Part Number	3403.0165.11	
Manufacturer	Schurter Inc.	
Category	Circuit Protection Fuses	
Description	FUSE BRD MNT 800MA 250VAC 125VDC	
Package	2-SMD, Square End Block	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



3403.0165.11 Specifications

Manufacturer Part Number 3403.0165.11 Manufacturer Schurter Inc. Category Circuit Protection Fuses Fuses Package 2-SMD, Square End Block Series UMT 250 Fuser Type Board Mount (Cartridge Style Excluded) Current Rating 800mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Package / Case 2-SMD, Square End Block Mounting Type Suface Mount Breaking Capacity @ Rated Voltage 200A AC, 35A DC Melting I2t 1.4 Approvals CQC, cURus, KC, UL, VDE Operating Temperature -55°C ~ 125°C Color - Color -			
CategoryCircuit ProtectionFusesPackage2-SMD, Square End BlockSeriesUMT 250Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating800mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t1.4ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm)	Manufacturer Part Number	3403.0165.11	
FusesPackage2-SMD, Square End BlockSeriesUMT 250Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating800mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t1.4ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Manufacturer	Schurter Inc.	
Package2-SMD, Square End BlockSeriesUMT 250Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating800mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage00A AC, 35A DCMelting 12t1.4ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor.Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm)	Category	Circuit Protection	
SeriesUMT 250Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating800mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t1.4ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating800mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t1.4ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor.Size / Dimension0398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm)	Package	2-SMD, Square End Block	
Current Rating800mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting 12t1.4ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor.Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm)	Series	UMT 250	
Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Package / Case 2-SMD, Square End Block Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 200A AC, 35A DC Melting I2t 1.4 Approvals CQC, cURus, KC, UL, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t1.4ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Current Rating	800mA	
Response TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t1.4ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Voltage Rating - AC	250V	
Package / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t1.4ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Voltage Rating - DC	125V	
Mounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t1.4ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Response Time	Slow	
Breaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t1.4ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Package / Case	2-SMD, Square End Block	
Melting I2t1.4ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Mounting Type	Surface Mount	
ApprovalsCQC, cURus, KC, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Breaking Capacity @ Rated Voltage	200A AC, 35A DC	
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Melting I2t	1.4	
Color - Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Approvals	CQC, cURus, KC, UL, VDE	
Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Operating Temperature	-55°C ~ 125°C	
	Color	-	
Report errors	Size / Dimension	0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	
Report croits		Rep	oort errors?

3403.0165.11 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 3403.0165.11, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com