

3403.0170.24

3403.0170.24 Information



Part Number	3403.0170.24	
Manufacturer	Schurter Inc.	
Category	Circuit Protection Fuses	
Description	FUSE BRD MNT 2.5A 250VAC 125VDC	
Package	2-SMD, Square End Block	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



3403.0170.24 Specifications

ManufacturerSchurter Inc.CategoryCircuit ProtectionFusesPackage2-SMD, Square End BlockSeriesUMT 250Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating2.5AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowPackage / Case2.SMD, Square End BlockMunting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t7.5ApprovalsCQC, cURus, KC, PSE/JET, UL, VDEOperating Temperature55°C ~ 125°C			
CategoryCircuit ProtectionFusesPackage2-SMD, Square End BlockSeriesUMT 250Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating2.5AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCApprovalsCQC, cURus, KC, PSE/JET, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Manufacturer Part Number	3403.0170.24	
Fuses Package 2-SMD, Square End Block Series UMT 250 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Package / Case 2-SMD, Square End Block Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 200A AC, 35A DC Melting 12t 7.5 Approvals CQC, cURus, KC, PSE/JET, UL, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Manufacturer	Schurter Inc.	
Package2-SMD, Square End BlockSeriesUMT 250Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating2.5AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t.55°C ~ 125°COperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm)	Category	Circuit Protection	
Series UMT 250 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Package / Case 2-SMD, Square End Block Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 200A AC, 35A DC Melting I2t 7.5 Approvals CQC, cURus, KC, PSE/JET, UL, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Fuse Type2.5AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowPackage / CaseSom Surface MountMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t7.5ApprovalsCQC, cURus, KC, PSE/JET, UL, VDEOperating Temperature-55°C ~ 125°CColor.Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm)	Package	2-SMD, Square End Block	
Current Rating 2.5A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Package / Case 2-SMD, Square End Block Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 200A AC, 35A DC Melting I2t 7.5 Approvals CQC, cURus, KC, PSE/JET, UL, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Series	UMT 250	
Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Package / Case Slow Nounting Type 2-SMD, Square End Block Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 200A AC, 35A DC Melting I2t 7.5 Approvals CQC, cURus, KC, PSE/JET, UL, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC125VResponse TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t7.5ApprovalsCQC, cURus, KC, PSE/JET, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Current Rating	2.5A	
Response TimeSlowPackage / Case2-SMD, Square End BlockMounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t7.5ApprovalsCQC, cURus, KC, PSE/JET, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Voltage Rating - AC	250V	
Package / Case 2-SMD, Square End Block Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 200A AC, 35A DC Melting I2t 7.5 Approvals CQC, cURus, KC, PSE/JET, UL, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Voltage Rating - DC	125V	
Mounting TypeSurface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t7.5ApprovalsCQC, cURus, KC, PSE/JET, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Response Time	Slow	
Breaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t7.5ApprovalsCQC, cURus, KC, PSE/JET, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Package / Case	2-SMD, Square End Block	
Melting I2t 7.5 Approvals CQC, cURus, KC, PSE/JET, UL, VDE Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Mounting Type	Surface Mount	
ApprovalsCQC, cURus, KC, PSE/JET, UL, VDEOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Breaking Capacity @ Rated Voltage	200A AC, 35A DC	
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Melting I2t	7.5	
Color - Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Approvals	CQC, cURus, KC, PSE/JET, UL, VDE	
Size / Dimension 0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	Operating Temperature	-55°C ~ 125°C	
	Color	-	
Report errors?	Size / Dimension	0.398" L x 0.118" W x 0.118" H (10.10mm x 3.00mm x 3.00mm)	
		Report	errors?

3403.0170.24 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 3403.0170.24, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com