

3404.2412.11

3404.2412.11 Information



Part Number	3404.2412.11	
Manufacturer	Schurter Inc.	
Category	Circuit Protection Fuses	
Description	FUSE BRD MNT 400MA 277VAC 250VDC	
Package	2-SMD, Square End Block with Clip	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



3404.2412.11 Specifications

Manufacturer Part Number3404.2412.11ManufacturerSchurter Inc.CategoryCircuit ProtectionFusesFusesPackage2-SMD, Square End Block with ClipSeriesUMZ 250Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating400mAVoltage Rating - AC250VPackage / CaseSlowPackage / Case2-SMD, Square End Block with ClipPackage / CaseSlowPackage / Case00A AC, 35A DCMounting Type044CPackage Jackator Oltage0.4SprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-Sire / Dimension0.445" L x 0.165" W x 0.157" H (11.30mm x 4.20mm x 4.00mm)			
CategoryCircuit ProtectionFusesPackage2-SMD, Square End Block with ClipSeriesUMZ 250Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating400mAVoltage Rating - AC277VVoltage Rating - DC50VResponse TimeSlowPackage / Case2-SMD, Square End Block with ClipMounting TypeHolder/Surface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t0.4ApprovalscuRus, VDEOperating Temperature4.0°C ~ 85°CColor-	Manufacturer Part Number	3404.2412.11	
FusesPackage2-SMD, Square End Block with ClipSeriesUMZ 250Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating400mAVoltage Rating - AC277VVoltage Rating - DC250VResponse TimeSlowPackage / Case2-SMD, Square End Block with ClipMounting TypeHolder/Surface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t0.4ApprovalscURus, VDEOperating Temperature40°C ~ 85°CColor-	Manufacturer	Schurter Inc.	
Package2-SMD, Square End Block with ClipSeriesUMZ 250Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating400mAVoltage Rating - AC277VVoltage Rating - DC50VResponse TimeSlowPackage / Case2-SMD, Square End Block with ClipMounting Type04Ac, 35A DCBreaking Capacity @ Rated Voltage04ApprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-	Category	Circuit Protection	
SeriesUMZ 250Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating400mAVoltage Rating - AC277VVoltage Rating - DC250VResponse TimeSlowPackage / Case2-SMD, Square End Block with ClipMounting TypeHolder/Surface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t0.4ApprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating400mAVoltage Rating - AC277VVoltage Rating - DC250VResponse TimeSlowPackage / Case2-SMD, Square End Block with ClipMounting TypeHolder/Surface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t0.4ApprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-	Package	2-SMD, Square End Block with Clip	
Current Rating400mAVoltage Rating - AC277VVoltage Rating - DC250VResponse TimeSlowPackage / Case2-SMD, Square End Block with ClipMounting TypeHolder/Surface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t0.4ApprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-	Series	UMZ 250	
Voltage Rating - AC277VVoltage Rating - DC250VResponse TimeSlowPackage / Case2-SMD, Square End Block with ClipMounting TypeHolder/Surface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t0.4ApprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC250VResponse TimeSlowPackage / Case2-SMD, Square End Block with ClipMounting TypeHolder/Surface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t0.4ApprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-	Current Rating	400mA	
Response TimeSlowPackage / Case2-SMD, Square End Block with ClipMounting TypeHolder/Surface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t0.4ApprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-	Voltage Rating - AC	277V	
Package / Case2-SMD, Square End Block with ClipMounting TypeHolder/Surface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t0.4ApprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-	Voltage Rating - DC	250V	
Mounting TypeHolder/Surface MountBreaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t0.4ApprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-	Response Time	Slow	
Breaking Capacity @ Rated Voltage200A AC, 35A DCMelting I2t0.4ApprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-	Package / Case	2-SMD, Square End Block with Clip	
Melting I2t0.4ApprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-	Mounting Type	Holder/Surface Mount	
ApprovalscURus, VDEOperating Temperature-40°C ~ 85°CColor-	Breaking Capacity @ Rated Voltage	200A AC, 35A DC	
Operating Temperature-40°C ~ 85°CColor-	Melting I2t	0.4	
Color -	Approvals	cURus, VDE	
	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Size / Dimension 0.445" L x 0.165" W x 0.157" H (11.30mm x 4.20mm x 4.00mm)	Color	-	
	Size / Dimension	0.445" L x 0.165" W x 0.157" H (11.30mm x 4.20mm x 4.00mm)	
Report err			Report errors?

3404.2412.11 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 3404.2412.11, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com