

3413.0008.26

3413.0008.26 Information



Part Number	3413.0008.26
Manufacturer	Schurter Inc.
Category	Circuit Protection Fuses
Description	FUSE BRD MNT 160MA 125VAC 63VDC
Package	1206 (3216 Metric)
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



3413.0008.26 Specifications

Manufacturer Part Number3413.0008.26ManufacturerSchurter Inc.CategoryCircuit ProtectionFusesPackage1206 (3216 Metric)SeriesUSFF 1206Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating160mAVoltage Rating - AC3413.0008.26Package / Case125VPackage / Case1206 (3216 Metric)Mounting TypeSurface MountPackang Capacity @ Rated Voltage100 AC, 100A DCMelting 12t0.0015ApprovalscJRusOperating Temperature.55°C ~ 90°CColor.			
CategoryCircuit Protection FusesPackage1206 (3216 Metric)Package1206 (3216 Metric)SeriesUSFF 1206Fuse TypeBoard Mount (Catridge Style Excluded)Current Rating160mAVoltage Rating - AC125VVoltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage10A AC, 100A DCMelting 12t0.0015ApprovalscURusOperating Temperature-55°C ~90°C	Manufacturer Part Number	3413.0008.26	
FusesPackage1206 (3216 Metric)SeriesUSFF 1206Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating160mAVoltage Rating - AC125VVoltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage0.0015ApprovalscURusOperating Temperature-55°C ~ 90°C	Manufacturer	Schurter Inc.	
Package1206 (3216 Metric)SeriesUSF 1206Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating160mAVoltage Rating - AC125VVoltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage0.0015ApprovalscURusOperating Temperature-55°C ~ 90°C	Category	Circuit Protection	
SeriesUSFF 1206Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating160mAVoltage Rating - AC125VVoltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage10A AC, 100A DCMelting I2t0.0015ApprovalscURusOperating Temperature-55°C ~ 90°C		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating160mAVoltage Rating - AC125VVoltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage10A AC, 100A DCMelting I2t0.0015ApprovalscURusOperating Temperature-55°C ~ 90°C	Package	1206 (3216 Metric)	
Current Rating160mAVoltage Rating - AC125VVoltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage10A AC, 100A DCMelting I2t0.0015ApprovalscURusOperating Temperature-55°C ~ 90°C	Series	USFF 1206	
Voltage Rating - AC125VVoltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage10A AC, 100A DCMelting I2t0.0015ApprovalscURusOperating Temperature-55°C ~ 90°C	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC63VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage10A AC, 100A DCMelting I2t0.0015ApprovalscURusOperating Temperature-55°C ~ 90°C	Current Rating	160mA	
Response TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage10A AC, 100A DCMelting I2t0.0015ApprovalscURusOperating Temperature-55°C ~ 90°C	Voltage Rating - AC	125V	
Package / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage10A AC, 100A DCMelting I2t0.0015ApprovalscURusOperating Temperature-55°C ~ 90°C	Voltage Rating - DC	63V	
Mounting TypeSurface MountBreaking Capacity @ Rated Voltage10A AC, 100A DCMelting I2t0.0015ApprovalscURusOperating Temperature-55°C ~ 90°C	Response Time	Fast	
Breaking Capacity @ Rated Voltage10A AC, 100A DCMelting I2t0.0015ApprovalscURusOperating Temperature-55°C ~ 90°C	Package / Case	1206 (3216 Metric)	
Melting I2t0.0015ApprovalscURusOperating Temperature-55°C ~ 90°C	Mounting Type	Surface Mount	
ApprovalscURusOperating Temperature-55°C ~ 90°C	Breaking Capacity @ Rated Voltage	10A AC, 100A DC	
Operating Temperature $-55^{\circ}\text{C} \sim 90^{\circ}\text{C}$	Melting I2t	0.0015	
	Approvals	cURus	
Color -	Operating Temperature	-55°C ~ 90°C	
	Color	-	
Size / Dimension 0.126" L x 0.063" W x 0.063" H (3.20mm x 1.60mm x 1.60mm)	Size / Dimension	0.126" L x 0.063" W x 0.063" H (3.20mm x 1.60mm x 1.60mm)	
Report errors?			Report errors?

3413.0008.26 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 3413.0008.26, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com