

342-062-521-202

342-062-521-202 Information

Heisener.com	Part Number Manufacturer Category Description Package	342-062-521-202 EDAC Inc. Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 62POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



342-062-521-202 Specifications

ManufacturerEDAC Inc.CardegoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series342Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Number of Positions/Bay/Row62Number of Positions0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact Type- <th>•</th> <th></th> <th></th>	•		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series342Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Number of Positions/Bay/Row62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact TypeGeneFauge FeatureFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature65°C ~ 125°C	Manufacturer Part Number	342-062-521-202	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series342Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialCooper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	EDAC Inc.	
Package-Series342Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact Type-Contact Type-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects	
Series342Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Number of Positions/Bay/Row62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact Finish ThicknessOoper, Nickel, Tin AlloyContact Finish Thickness-Contact Type-Contact Type-Fange FeatureFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row31Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact TypeGreenFlange FeatureFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature65° C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row31Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type100" (2.54mm)Contact MaterialSolderContact FinishGoldContact Finish Thickness-Contact Type-Contact Type-Features-PitchGoldContact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Series	342	
Number of Positions/Bay/Row31Number of Positions62Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness-Contact Spee-Contact Finish Thickness-ColorGreenFlange FeatureFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Contact Material Solder Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-TerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	31	
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	62	
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)	
TerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole	
Contact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Copper, Nickel, Tin Alloy	
Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	-	
Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	-	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Green	
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
			Report errors?

342-062-521-202 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

If you have any question about 342-062-521-202, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com