

### 345-020-540-802 Information

Heisener.com

Part Number 345-020-540-802 Manufacturer EDAC Inc.

**Category** Connectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 20POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **345-020-540-802 Specifications**

Manufacturer Part Number         345-020-540-802           Manufacturer         EDAC Inc.           Category         Connectors, Interconnects           Package         -           Series         345           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         10           Number of Positions         20           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Wire Wrap           Contact Material         Copper, Nickel, Tin Alloy           Contact Finish         Gold           Contact Tinish Thickness         -           Cotact Type         -           Color         Green           Flange Feature         Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia           Operating Temperature         -65°C ~ 105°C	•	
Category         Connectors, Interconnects           Package         -           Series         345           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         10           Number of Positions         20           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Wire Wrap           Contact Material         Copper, Nickel, Tin Alloy           Contact Finish         Gold           Contact Type         -           Color         Green           Flange Feature         Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia           Operating Temperature         -65°C ~ 105°C	Manufacturer Part Number	345-020-540-802
Package         -           Series         345           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         10           Number of Positions         20           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Wire Wrap           Contact Material         Copper, Nickel, Tin Alloy           Contact Finish         Gold           Contact Type         -           Color         Green           Flange Feature         Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia           Operating Temperature         -65°C ~ 105°C	Manufacturer	EDAC Inc.
Package         -           Series         345           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         10           Number of Positions         20           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Wire Wrap           Contact Material         Copper, Nickel, Tin Alloy           Contact Finish         Gold           Contact Finish Thickness         -           Contact Type         -           Color         Green           Flange Feature         Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia           Operating Temperature         -65°C ~ 105°C	Category	Connectors, Interconnects
Series 345 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 10 Number of Positions 20 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Package	-
Gender Female  Number of Positions/Bay/Row 10  Number of Positions 20  Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.100" (2.54mm)  Features -  Mounting Type Through Hole  Termination Wire Wrap  Contact Material Copper, Nickel, Tin Alloy  Contact Finish Gold  Contact Finish Thickness -  Contact Type -  Color Green  Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia  Operating Temperature -65°C ~ 105°C	Series	345
Number of Positions/Bay/Row10Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Card Type	Non Specified - Dual Edge
Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Gender	Female
Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.100" (2.54mm)  Features - Mounting Type Through Hole  Termination Wire Wrap  Contact Material Copper, Nickel, Tin Alloy  Contact Finish Thickness - Contact Type - Color Green  Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia  Operating Temperature -65°C ~ 105°C	Number of Positions/Bay/Row	10
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Number of Positions	20
Pitch 0.100" (2.54mm)  Features -  Mounting Type Through Hole  Termination Wire Wrap  Contact Material Copper, Nickel, Tin Alloy  Contact Finish Gold  Contact Finish Thickness -  Contact Type -  Color Green  Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia  Operating Temperature -65°C ~ 105°C	Card Thickness	0.062" (1.57mm)
Features - Mounting Type Through Hole  Termination Wire Wrap  Contact Material Copper, Nickel, Tin Alloy  Contact Finish  Contact Finish Thickness - Contact Type  Color Green  Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia  Operating Temperature -65°C ~ 105°C	Number of Rows	2
Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Pitch	0.100" (2.54mm)
Termination Wire Wrap  Contact Material Copper, Nickel, Tin Alloy  Contact Finish Gold  Contact Finish Thickness -  Contact Type -  Color Green  Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia  Operating Temperature -65°C ~ 105°C	Features	-
Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Operating Temperature  Copper, Nickel, Tin Alloy Gold Gold Contact Type - Color Green Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Coperating Temperature	Mounting Type	Through Hole
Contact Finish  Contact Finish Thickness  Contact Type  Color  Green  Flange Feature  Operating Temperature  Gold  Gold  Contact Type  - Color  Green  Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia  -65°C ~ 105°C	Termination	Wire Wrap
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Contact Material	Copper, Nickel, Tin Alloy
Contact Type - Color Green  Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Contact Finish	Gold
Color Green  Flange Feature Top Mount Opening, Unthreaded, $0.128$ " (3.25mm) Dia  Operating Temperature $-65$ °C $\sim 105$ °C	Contact Finish Thickness	-
Flange Feature Top Mount Opening, Unthreaded, $0.128$ " (3.25mm) Dia Operating Temperature $-65$ °C $\sim 105$ °C	Contact Type	-
Operating Temperature $-65^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Color	Green
• • •	Flange Feature	Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia
Report errors?	Operating Temperature	-65°C ~ 105°C
		Report errors?

### 345-020-540-802 Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 345-020-540-802 Payment Methods



















## 345-020-540-802 Shipping Methods













If you have any question about 345-020-540-802, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com