

345-072-520-802 Information

Heisener.com

Part Number 345-072-520-802 Manufacturer EDAC Inc.

Category Connectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 72POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









		G 101	. •
345-072	-520-802	Specifica	tions

Manufacturer Part Number 345-072-520-802 Manufacturer EDAC Inc. Category Connectors, Interconnects Package - Series 345 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Tipish Gold Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	•		
Category Connectors, Interconnects Package - Series 345 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Manufacturer Part Number	345-072-520-802	
Package - Series 345 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Manufacturer	EDAC Inc.	
Package - Series 345 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Category	Connectors, Interconnects	
Series 345 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row36Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-CotorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row 36 Number of Positions 72 Card Thickness $0.062"$ (1.57mm)Number of Rows 2 Pitch $0.100"$ (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, $0.128"$ (3.25mm) DiaOperating Temperature -65° C $\sim 105^{\circ}$ C	Series	345	
Number of Positions/Bay/Row 36 Number of Positions 72 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Card Type	Non Specified - Dual Edge	
Number of Positions72Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Gender	Female	
Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Number of Positions/Bay/Row	36	
Number of Rows Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Number of Positions	72	
Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Card Thickness	0.062" (1.57mm)	
Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Contact Finish Thickness - Contact Type Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Pitch	0.100" (2.54mm)	
Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Features	-	
Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Operating Temperature Copper, Nickel, Tin Alloy Gold Cold Cold Cold Contact Type - Color Green Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Cold Copperating Temperature Copper, Nickel, Tin Alloy Cold Cold Cold Contact Finish Thickness - Contact Type - Color Color	Mounting Type	Through Hole	
Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Termination	Solder	
Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Contact Material	Copper, Nickel, Tin Alloy	
Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128 " (3.25 mm) Dia Operating Temperature -65 °C ~ 105 °C	Contact Finish	Gold	
Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128 " (3.25 mm) Dia Operating Temperature -65 °C ~ 105 °C	Contact Finish Thickness	-	
Flange Feature Top Mount Opening, Unthreaded, 0.128 " (3.25 mm) Dia Operating Temperature -65 °C ~ 105 °C	Contact Type	-	
Operating Temperature $-65^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Color	Green	
	Flange Feature	Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 105°C	
		Report errors?	

345-072-520-802 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

345-072-520-802 Payment Methods



















345-072-520-802 Shipping Methods













If you have any question about 345-072-520-802, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com