

345-086-520-802 Information

Heisener.com

Part Number 345-086-520-802 Manufacturer EDAC Inc.

Category Connectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 86POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









345-086-520-802 Specifications

Manufacturer Part Number 345-086-520-802 Manufacturer EDAC Inc. Category Connectors, Interconnects Package - Series 345 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Tipsh Gold Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	•	
Category Connectors, Interconnects Package - Series 345 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Manufacturer Part Number	345-086-520-802
Package - Series 345 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Manufacturer	EDAC Inc.
Package - Series 345 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Category	Connectors, Interconnects
Series345Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Package	-
GenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Series	345
Number of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Card Type	Non Specified - Dual Edge
Number of Positions Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type Color Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Number of Positions/Bay/Row	43
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Number of Positions	86
Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Operating Temperature -65°C ~ 105°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 105°C	Pitch	0.100" (2.54mm)
Termination Solder Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Features	-
Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Mounting Type	Through Hole
Contact Finish Contact Finish Thickness Contact Type Color Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Termination	Solder
Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Contact Material	Copper, Nickel, Tin Alloy
Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 105°C	Contact Finish	Gold
Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128 " (3.25 mm) Dia Operating Temperature -65 °C ~ 105 °C	Contact Finish Thickness	-
Flange Feature Top Mount Opening, Unthreaded, 0.128 " (3.25mm) Dia Operating Temperature -65 °C ~ 105 °C	Contact Type	-
Operating Temperature $-65^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Color	Green
	Flange Feature	Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia
Report errors?	Operating Temperature	-65°C ~ 105°C
		Report errors?

345-086-520-802 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

345-086-520-802 Payment Methods



















345-086-520-802 Shipping Methods













If you have any question about 345-086-520-802, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com