

346-100-541-802 Information

Heisener.com

Part Number 346-100-541-802 Manufacturer EDAC Inc.

Category Connectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 100POS .125

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









346-100-541-802 Specifications

Manufacturer Part Number 346-100-541-802 Manufacturer EDAC Inc. Category Connectors, Interconnects Package - Series 346 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Tipish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 125°C	•	
Category Connectors, Interconnects Package - Series 346 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	346-100-541-802
Package - Series 346 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer	EDAC Inc.
Package - Series 346 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects
Series346Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Series	346
Number of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Contact Material Copper, Nickel, Tin Alloy Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 125°C	Number of Positions/Bay/Row	50
Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	100
Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole Termination Wire Wrap Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Operating Temperature -65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.125" (3.18mm)
Termination Wire Wrap Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 125°C	Features	-
Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 125°C	Mounting Type	Through Hole
Contact Finish Contact Finish Thickness Contact Type Color Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 125°C	Termination	Wire Wrap
Contact Finish Thickness - Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 125°C	Contact Material	Copper, Nickel, Tin Alloy
Contact Type - Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color Green Flange Feature Top Mount Opening, Unthreaded, 0.128 " (3.25 mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Finish Thickness	-
Flange Feature Top Mount Opening, Unthreaded, 0.128 " (3.25mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Type	-
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Green
	Flange Feature	Top Mount Opening, Unthreaded, 0.128" (3.25mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

346-100-541-802 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

346-100-541-802 Payment Methods



















346-100-541-802 Shipping Methods













If you have any question about 346-100-541-802, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com