

346-83-103-41-036101

346-83-103-41-036101 Information



For Reference Only

Part Number	346-83-103-41-036101
Manufacturer	Preci-Dip
Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets
Description	PCB CONN PRESS FIT 2.54MM
Package	-
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



346-83-103-41-036101 Specifications

Manufacturer Part Number346-83-103-41-036101ManufacturerPreci-DipCategoryConnectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series346Connector TypeSocketContact TypeBoardSoute of PositionsSocketNumber of Positions LoadedAllNumber of Rows1Number of Rows0.100" (2.54mm)Number of Rows1TerminationPress-Fit, SolderNumber TypeSocketSoctat Fithish - MatingGoldContact Fithish - MatingSolderSolder Fithish - MatingSolderStation ColorJackStation Fithish - MatingSolderSolder Fithish - MatingSolderContact Fithish - MatingSolderContact Fithish - MatingSolderSolder Fithish - MatingSolderSolder Fithish - MatingSolderContact Fithish - MatingSolderSolder Fithish - MatingSolder <t< th=""><th></th><th></th></t<>		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series346Connector TypeSocketContact TypeBoard to BoardNumber of Positions3Number of Positions LoadedAllNumber of Rows1Number of Rows1Number of Rows1Number of RowsPress-Fit, SolderNumber of Positions0100" (2.54mm)Number of Rows1Row Spacing - Mating-Poss-Fit, SolderPress-Fit, SolderFastening TypePosh-PullContact Finish - Mating0.6dContact Finish Thickness - Mating9.5µin (0.75µm)Insulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Manufacturer Part Number	346-83-103-41-036101
Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series 346 Connector Type Socket Contact Type Board to Board Style Board to Board Number of Positions 3 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Yermination Press-Fit, Solder Fastening Type Qual Contact Finish - Mating Gold Contact Finish Thickness - Mating 9.5µún (0.75µm) Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.110" (2.79mm)	Manufacturer	Preci-Dip
Package.Series346Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions3Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening Type0.104 (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating9.55µ(0.75µm)Insulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature55°C ~ 125°C	Category	Connectors, Interconnects
Series346Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions3Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypeGoldContact Finish - Mating9.5yin (0.75µm)Insulation ColorBlackInsulation Height0.110" (2.79mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions3Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderRotact Finish - MatingGoldContact Finish - Mating9.5jun (0.75µm)Insulation ColorBlackInsulation Height0.10" (2.79mm)Operating Temperature55°C ~ 125°C	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions3Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypeGoldContact Finish - Mating29.5µin (0.75µm)Insulation ColorBlackInsulation Height0.110" (2.79mm)Contact Length - Post0.110" (2.79mm)	Series	346
StyleBoard to BoardNumber of Positions3Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypeOldContact Finish - MatingGoldContact Finish Thickness - Mating9.5µin (0.75µm)Insulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Connector Type	Socket
Number of Positions 3 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 9.5µin (0.75µm) Insulation Color Black Insulation Height 0.110" (2.79mm) Operating Temperature -55°C ~ 125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.110" (2.79mm)Contact Length - Post0.55°C ~ 125°C	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Number of Positions	3
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5µin (0.75µm)Insulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating9.5µin (0.75µm)Insulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5µin (0.75µm)Insulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Number of Rows	1
TerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	-
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5µin (0.75µm)Insulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating29.5µin (0.75µm)Insulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Termination	Press-Fit, Solder
Contact Finish Thickness - Mating29.5µin (0.75µm)Insulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.173" (4.40mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	29.5µin (0.75µm)
Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.173" (4.40mm)
	Contact Length - Post	0.110" (2.79mm)
	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

346-83-103-41-036101 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

346-83-103-41-036101 Payment Methods WIRE Transfer PayPal William Methods 346-83-103-41-036101 Shipping Methods Image Feedex. Image Of PayPal Ender

If you have any question about 346-83-103-41-036101, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com