

346-87-162-41-035101 Information



For Reference Only

Part Number 346-87-162-41-035101

Manufacturer Preci-Dip

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description PCB CONN PRESS FIT 2.54MM

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









346-87-162-41-035101 Specifications

Manufacturer Part Number 346-87-162-41-035101 Manufacturer Preci-Dip Category Connectors, Interconnects Package - Series 346 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 62 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C Material Flammability Rating UL94 V-0				
Category Connectors, Interconnects Package - Series 346 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 62 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Manufacturer Part Number	346-87-162-41-035101		
Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series 346 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.150" (3.81mm) Coperating Temperature - 55°C ~ 125°C	Manufacturer	Preci-Dip		
Package - Series 346 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 62 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Category	Connectors, Interconnects		
Series 346 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 62 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets		
Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions62Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Package	-		
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions62Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Series	346		
StyleBoard to BoardNumber of Positions62Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Connector Type	Socket		
Number of Positions 62 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Contact Type	Female Socket		
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board		
Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Number of Positions	62		
Number of Rows Row Spacing - Mating	Number of Positions Loaded	All		
Row Spacing - Mating Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature	Pitch - Mating	0.100" (2.54mm)		
Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Number of Rows	1		
Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Row Spacing - Mating	-		
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Mounting Type	Through Hole		
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Termination	Press-Fit, Solder		
Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.173" (4.40mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Fastening Type	Push-Pull		
Insulation ColorBlackInsulation Height $0.173"$ (4.40mm)Contact Length - Post $0.150"$ (3.81mm)Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish - Mating	Gold		
Insulation Height $0.173"$ (4.40mm)Contact Length - Post $0.150"$ (3.81mm)Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	Flash		
Contact Length - Post $0.150"$ (3.81mm) Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black		
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.173" (4.40mm)		
	Contact Length - Post	0.150" (3.81mm)		
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C		
	Material Flammability Rating	UL94 V-0		

Contact Finish - Post	Tin		
Mated Stacking Heights	-		
Ingress Protection	-		
Features	-		
			Report errors?

346-87-162-41-035101 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

346-87-162-41-035101 Payment Methods



















346-87-162-41-035101 Shipping Methods













If you have any question about 346-87-162-41-035101, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com