

34ASP18T7M1RT

34ASP18T7M1RT Information

Heisener.com

Part Number 34ASP18T7M1RT

Manufacturer Grayhill Inc.

Switches Category Toggle Switches

Description SWITCH TOGGLE SPDT 0.4VA 20V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









34ASP18T7M1RT Specifications

Manufacturer Part Number 34ASP18T7M1RT Manufacturer Grayhill Inc. Category Switches Toggle Switches Package - Series 34A Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -		
Category Switches Toggle Switches Package - Series 34A Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round Actuator Length Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Switches Toggle Switches - SPDT SAPA SAPA SAPA SAPA SAPA SAPA SAPA SAP	Manufacturer Part Number	34ASP18T7M1RT
Package Series 34A Circuit SPDT Switch Function On-On Current Rating Otltage Rating - AC Voltage Rating - DC Actuator Type Actuator Length Illumination Illumination Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection TigpDT 34A CO On-On On On-On On On-On On O	Manufacturer	Grayhill Inc.
Package - Series 34A Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection -	Category	Switches
Series 34A Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection -		Toggle Switches
CircuitSPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-	Package	-
Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection -	Series	34A
Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection	Circuit	SPDT
Voltage Rating - AC Voltage Rating - DC 20V Actuator Type Standard Round 17.45mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread Ingress Protection 20V 20V 20V 20V 20V 20V 20V 20	Switch Function	On-On
Voltage Rating - DC Actuator Type Standard Round 17.45mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Sushing Thread Ingress Protection 20V Standard Round Standard Round 17.45mm Non-Illuminated - - - - - Standard Round Non-Illuminated Panel Mount Solder Lug Solder Lug - - - Illumination Style Solder Lug - - - Ingress Protection - - - - - - - - - - - - -	Current Rating	0.4VA (AC/DC)
Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection -	Voltage Rating - AC	20V
Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection -	Voltage Rating - DC	20V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection -	Actuator Length	17.45mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection -	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection -	Mounting Type	Panel Mount
Bushing Thread 15/32-32 Ingress Protection -	Termination Style	Solder Lug
Ingress Protection -	Panel Cutout Dimensions	Circular - 11.91mm Dia
	Bushing Thread	15/32-32
Features -	Ingress Protection	-
	Features	-
Report errors?		Report errors?

34ASP18T7M1RT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

34ASP18T7M1RT Payment Methods



















34ASP18T7M1RT Shipping Methods













If you have any question about 34ASP18T7M1RT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com