



34D505D450FJ0 Information

Heisener.com

Part Number 34D505D450FJ0
Manufacturer Vishay Sprague
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 5UF 450V AXIAL

Package Axial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









34D505D450FJ0 Specifications

Manufacturer Part Number 34D505D450F10 Manufacturer Vishay Sprague Category Capacitors Aluminum Electrolytic Capacitors Package Axial, Can Series 34D Capacitance 5μF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) 41 Ohm Lifetime @ Temp. - Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 93mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.625" Dia x 1.625" L (15.88mm x 41.28mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Axial, Can Series 34D Capacitance 5μF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) 41 Ohm Lifetime @ Temp. - Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 93mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.625" Dia x 1.625" L (15.88mm x 41.28mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Manufacturer Part Number	34D505D450FJ0
Aluminum Electrolytic Capacitors Package Axial, Can Series 34D Capacitance 5μF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Pakes Axial, Can	Manufacturer	Vishay Sprague
PackageAxial, CanSeries34DCapacitance5μFTolerance-10%, +50%Voltage - Rated450VESR (Equivalent Series Resistance)41 OhmLifetime @ TempOperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency93mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension0.625" Dia x 1.625" L (15.88mm x 41.28mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Category	Capacitors
Series 34D Capacitance 5µF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) 41 Ohm Lifetime @ Temp Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 93mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.625" Dia x 1.625" L (15.88mm x 41.28mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can		Aluminum Electrolytic Capacitors
Capacitance 5µF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) 41 Ohm Lifetime @ Temp Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 93mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.625" Dia x 1.625" L (15.88mm x 41.28mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Package	Axial, Can
Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) 41 Ohm Lifetime @ Temp Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 93mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.625" Dia x 1.625" L (15.88mm x 41.28mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Series	34D
Voltage - Rated 450V ESR (Equivalent Series Resistance) 41 Ohm Lifetime @ Temp Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 93mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.625" Dia x 1.625" L (15.88mm x 41.28mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Capacitance	5μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Polar - C At Ohm At Oh A	Tolerance	-10%, +50%
Lifetime @ Temp. Operating Temperature - Polarization Polar Applications General Purpose Ripple Current - Low Frequency 93mA @ 120Hz Ripple Current - High Frequency Impedance - Lead Spacing - Size / Dimension 0.625" Dia x 1.625" L (15.88mm x 41.28mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Voltage - Rated	450V
Operating Temperature Polarization Polarization Applications General Purpose Ripple Current - Low Frequency Polar Ripple Current - High Frequency Ripple Current - High Frequency Frequenc	ESR (Equivalent Series Resistance)	41 Ohm
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency	Lifetime @ Temp.	-
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case General Purpose 93mA @ 120Hz - 0.625" Line Purpose - 0.625" Line Purpose 1.00 1.	Operating Temperature	-
Ripple Current - Low Frequency 93mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.625" Dia x 1.625" L (15.88mm x 41.28mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case - Axial, Can	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 0.625" Dia x 1.625" L (15.88mm x 41.28mm) Height - Seated (Max) - Surface Mount Land Size - Through Hole Package / Case Axial, Can	Ripple Current - Low Frequency	93mA @ 120Hz
Lead Spacing - Size / Dimension 0.625" Dia x 1.625" L (15.88mm x 41.28mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.625" Dia x 1.625" L (15.88mm x 41.28mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Axial, Can	Lead Spacing	-
Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Size / Dimension	0.625" Dia x 1.625" L (15.88mm x 41.28mm)
Mounting Type Through Hole Package / Case Axial, Can	Height - Seated (Max)	-
Package / Case Axial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Axial, Can
		Report errors?

34D505D450FJ0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

34D505D450FJ0 Payment Methods



















34D505D450FJ0 Shipping Methods













If you have any question about 34D505D450FJ0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com