

3501-12-511 Information

Heisener.com

Part Number 3501-12-511 **Manufacturer** Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED SPST 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3501-12-511 Specifications

Manufacturer Part Number3501-12-511ManufacturerCoto TechnologyCategoryRelaysPackage-Series3500Relay TypeReedCoil TypeNon LatchingCoil Current6mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin		
Category Relays Signal Relays, Up to 2 Amps - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 6mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 7 y VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Termination Style Relays 3500 A Signal Relays, Up to 2 Amps Seod - Substitute 2 Amps - Seod - Se	Manufacturer Part Number	3501-12-511
Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 6mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC	Manufacturer	Coto Technology
Package-Series3500Relay TypeReedCoil TypeNon LatchingCoil Current6mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 6mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current6mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current6mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Series	3500
Coil Current Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 7 UNDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Current	6mA
Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style 200VAC, 200VDC - Max 9 VDC 1 VDC 0.75ms Release Time 0.75ms Peatures Peatur	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	200VAC, 200VDC - Max
Operate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	9 VDC
Release Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	1 VDC
Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Operate Time	0.75ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	0.1ms
Termination Style PC Pin	Features	Sealed - Hermetically
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

3501-12-511 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3501-12-511 Payment Methods



















3501-12-511 Shipping Methods













If you have any question about 3501-12-511, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com