

3501-12-710 Information

Heisener.com

Part Number 3501-12-710 Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED SPST 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3501-12-710 Specifications

Manufacturer Part Number 3501-12-710 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 6mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole		
Category Relays Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 6mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically	Manufacturer Part Number	3501-12-710
Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 6mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically	Manufacturer	Coto Technology
Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 6mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically	Category	Relays
Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 6mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current6mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.75msRelease Time0.1msFeaturesSealed - Hermetically	Package	-
Coil TypeNon LatchingCoil Current6mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.75msRelease Time0.1msFeaturesSealed - Hermetically	Series	3500
Coil Current Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically	Relay Type	Reed
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically	Coil Current	6mA
Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically	Coil Voltage	12VDC
Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 9 VDC 1 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically	Switching Voltage	200VAC, 200VDC - Max
Operate Time0.75msRelease Time0.1msFeaturesSealed - Hermetically	Turn On Voltage (Max)	9 VDC
Release Time 0.1ms Features Sealed - Hermetically	Turn Off Voltage (Min)	1 VDC
Features Sealed - Hermetically	Operate Time	0.75ms
	Release Time	0.1ms
Mounting Type Through Hole	Features	Sealed - Hermetically
· · ·	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

3501-12-710 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3501-12-710 Payment Methods





















3501-12-710 Shipping Methods













If you have any question about 3501-12-710, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com