

### 3502-05-910 Information

Heisener.com

Part Number 3502-05-910 Manufacturer Coto Technology

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY REED DPST 500MA 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **3502-05-910 Specifications**

| Manufacturer Part Number         3502-05-910           Manufacturer         Coto Technology           Category         Relays           Signal Relays, Up to 2 Amps           Package         -           Series         3500           Relay Type         Reed           Coil Type         Non Latching           Coil Current         14.28mA           Coil Voltage         5VDC           Contact Form         DPST (2 Form A)           Contact Rating (Current)         500mA           Switching Voltage         200VAC, 200VDC - Max           Turn On Voltage (Max)         3.8 VDC           Turn Off Voltage (Min)         0.4 VDC           Operate Time         0.75ms           Release Time         0.1ms           Features         Sealed - Hermetically           Mounting Type         Through Hole           Termination Style         PC Pin  |                          |                             |
|--|--------------------------|-----------------------------|
| CategoryRelaysPackage-Series3500Relay TypeReedCoil TypeNon LatchingCoil Current14.28mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin   | Manufacturer Part Number | 3502-05-910                 |
| Package         -           Series         3500           Relay Type         Reed           Coil Type         Non Latching           Coil Current         14.28mA           Coil Voltage         5VDC           Contact Form         DPST (2 Form A)           Contact Rating (Current)         500mA           Switching Voltage         200VAC, 200VDC - Max           Turn On Voltage (Max)         3.8 VDC           Turn Off Voltage (Min)         0.4 VDC           Operate Time         0.75ms           Release Time         0.1ms           Features         Sealed - Hermetically           Mounting Type         Through Hole           Termination Style         PC Pin  | Manufacturer             | Coto Technology             |
| Package         -           Series         3500           Relay Type         Reed           Coil Type         Non Latching           Coil Current         14.28mA           Coil Voltage         5VDC           Contact Form         DPST (2 Form A)           Contact Rating (Current)         500mA           Switching Voltage         200VAC, 200VDC - Max           Turn On Voltage (Max)         3.8 VDC           Turn Off Voltage (Min)         0.4 VDC           Operate Time         0.75ms           Release Time         0.1ms           Features         Sealed - Hermetically           Mounting Type         Through Hole           Termination Style         PC Pin  | Category                 | Relays                      |
| Series         3500           Relay Type         Reed           Coil Type         Non Latching           Coil Current         14.28mA           Coil Voltage         5VDC           Contact Form         DPST (2 Form A)           Contact Rating (Current)         500mA           Switching Voltage         200VAC, 200VDC - Max           Turn On Voltage (Max)         3.8 VDC           Turn Off Voltage (Min)         0.4 VDC           Operate Time         0.75ms           Release Time         0.1ms           Features         Sealed - Hermetically           Mounting Type         Through Hole           Termination Style         PC Pin  |                          | Signal Relays, Up to 2 Amps |
| Relay TypeReedCoil TypeNon LatchingCoil Current14.28mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin   | Package                  | -                           |
| Coil TypeNon LatchingCoil Current14.28mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin   | Series                   | 3500                        |
| Coil Current Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin   | Relay Type               | Reed                        |
| Coil Voltage 5VDC  Contact Form DPST (2 Form A)  Contact Rating (Current) 500mA  Switching Voltage 200VAC, 200VDC - Max  Turn On Voltage (Max) 3.8 VDC  Turn Off Voltage (Min) 0.4 VDC  Operate Time 0.75ms  Release Time 0.1ms  Features Sealed - Hermetically  Mounting Type Through Hole  Termination Style PC Pin  | Coil Type                | Non Latching                |
| Contact Form DPST (2 Form A)  Contact Rating (Current) 500mA  Switching Voltage 200VAC, 200VDC - Max  Turn On Voltage (Max) 3.8 VDC  Turn Off Voltage (Min) 0.4 VDC  Operate Time 0.75ms  Release Time 0.1ms  Features Sealed - Hermetically  Mounting Type Through Hole  Termination Style PC Pin   | Coil Current             | 14.28mA                     |
| Contact Rating (Current)  Switching Voltage  200VAC, 200VDC - Max  Turn On Voltage (Max)  3.8 VDC  Turn Off Voltage (Min)  0.4 VDC  Operate Time  0.75ms  Release Time  0.1ms  Features  Sealed - Hermetically  Mounting Type  Through Hole  Termination Style   | Coil Voltage             | 5VDC                        |
| Switching Voltage  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  On Voltage (Min)  Operate Time  On Voltage (Min)  On Volta | Contact Form             | DPST (2 Form A)             |
| Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  O.75ms  Release Time  O.1ms  Features  Sealed - Hermetically  Mounting Type  Through Hole  Termination Style  3.8 VDC  0.4 VDC  0.75ms  Sealed - Hermetically  PC Pin   | Contact Rating (Current) | 500mA                       |
| Turn Off Voltage (Min)  Operate Time  O.75ms  Release Time  O.1ms  Features  Sealed - Hermetically  Mounting Type  Through Hole  Termination Style  PC Pin   | Switching Voltage        | 200VAC, 200VDC - Max        |
| Operate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin   | Turn On Voltage (Max)    | 3.8 VDC                     |
| Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin  | Turn Off Voltage (Min)   | 0.4 VDC                     |
| Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin   | Operate Time             | 0.75ms                      |
| Mounting Type Through Hole Termination Style PC Pin  | Release Time             | 0.1ms                       |
| Termination Style PC Pin   | Features                 | Sealed - Hermetically       |
|  | Mounting Type            | Through Hole                |
| Report errors?   | Termination Style        | PC Pin                      |
|  |                          | Report errors?              |

#### 3502-05-910 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **3502-05-910 Payment Methods**



















# **3502-05-910 Shipping Methods**













If you have any question about 3502-05-910, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com