

3502-05-911 Information

Heisener.com

Part Number 3502-05-911 Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED DPST 500MA 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3502-05-911 Specifications

Manufacturer Part Number 3502-05-911 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 14.28mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-Series3500Relay TypeReedCoil TypeNon LatchingCoil Current14.28mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	3502-05-911
Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 14.28mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Coto Technology
Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 14.28mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 14.28mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current14.28mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current14.28mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Series	3500
Coil Current Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Current	14.28mA
Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage 200VAC, 200VDC - Max 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.75ms Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style 200VAC, 200VDC - Max 3.8 VDC 0.4 VDC 0.75ms PC Pin	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time O.75ms Release Time O.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style 3.8 VDC 0.4 VDC 0.75ms Sealed - Hermetically PC Pin	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time O.75ms Release Time O.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	200VAC, 200VDC - Max
Operate Time0.75msRelease Time0.1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.8 VDC
Release Time 0.1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.4 VDC
Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Operate Time	0.75ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	0.1ms
Termination Style PC Pin	Features	Sealed - Hermetically
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

3502-05-911 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3502-05-911 Payment Methods



















3502-05-911 Shipping Methods













If you have any question about 3502-05-911, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com