

350826-1 Information

www,heisener.com

For Reference Only

Part Number 350826-1

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN HEADER 4POS VERT .250 TIN

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









350826-1 Specifications

Manufacturer Part Number 350826-1 Manufacturer TE Connectivity AMP Connectors Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series Universal MATE-N-LOK Connector Type Header Contact Type Female Socket Style Board to Cable/Wire Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.250" (6.35mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color White Insulation Height 0.550" (13.97mm)		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series Universal MATE-N-LOK Connector Type Header Contact Type Female Socket Style Board to Cable/Wire Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.250" (6.35mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Fastening Type Locking Ramp Contact Finish - Mating Tin Contact Finish Thickness - Mating Insulation Color White	Manufacturer Part Number	350826-1
Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series Universal MATE-N-LOK Connector Type Header Contact Type Female Socket Style Board to Cable/Wire Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.250" (6.35mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Tin Contact Finish Thickness - Mating Insulation Color White	Manufacturer	TE Connectivity AMP Connectors
Package - Series Universal MATE-N-LOK Connector Type Header Contact Type Female Socket Style Board to Cable/Wire Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.250" (6.35mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color White	Category	Connectors, Interconnects
Series Universal MATE-N-LOK Connector Type Header Contact Type Female Socket Style Board to Cable/Wire Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.250" (6.35mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color White		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Female Socket Style Board to Cable/Wire Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.250" (6.35mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color White	Package	-
Contact Type Female Socket Style Board to Cable/Wire Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.250" (6.35mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color White	Series	Universal MATE-N-LOK
Style Board to Cable/Wire Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.250" (6.35mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Tin Contact Finish Thickness - Mating Insulation Color White	Connector Type	Header
Number of Positions	Contact Type	Female Socket
Number of Positions Loaded All Pitch - Mating 0.250" (6.35mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color White	Style	Board to Cable/Wire
Pitch - Mating 0.250" (6.35mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color White	Number of Positions	4
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeLocking RampContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorWhite	Number of Positions Loaded	All
Row Spacing - Mating Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color White	Pitch - Mating	0.250" (6.35mm)
Mounting TypeThrough HoleTerminationSolderFastening TypeLocking RampContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorWhite	Number of Rows	1
Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color White	Row Spacing - Mating	-
Fastening Type Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Locking Ramp Tin White	Mounting Type	Through Hole
Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color White	Termination	Solder
Contact Finish Thickness - Mating Insulation Color White	Fastening Type	Locking Ramp
Insulation Color White	Contact Finish - Mating	Tin
	Contact Finish Thickness - Mating	-
Insulation Height 0.550" (13.97mm)	Insulation Color	White
	Insulation Height	0.550" (13.97mm)
Contact Length - Post 0.155" (3.94mm)	Contact Length - Post	0.155" (3.94mm)
Operating Temperature -	Operating Temperature	-
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

350826-1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

350826-1 Payment Methods



















350826-1 Shipping Methods













If you have any question about 350826-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com