

3520-05-111 Information

Heisener.com

Part Number 3520-05-111
Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED DPST 1A 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3520-05-111 Specifications

Manufacturer Part Number 3520-05-111 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 1A Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 2ms Release Time Ims Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin		
Category Relays Signal Relays, Up to 2 Amps - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage SvDC Contact Form DPST (2 Form A) Contact Rating (Current) 1A Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 2ms Release Time 1ms Features Sealed - Hermetically Mounting Type Termination Style Relays 3500 Relays Signal Relays, Up to 2 Amps 800 800 800 800 800 800 800 800 800 8	Manufacturer Part Number	3520-05-111
Package-Series3500Relay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)1ASwitching Voltage500VAC, 500VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time2msRelease Time1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Coto Technology
Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 1A Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 2ms Release Time 1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 1A Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 2ms Release Time Ims Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)1ASwitching Voltage500VAC, 500VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time2msRelease Time1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)1ASwitching Voltage500VAC, 500VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time2msRelease Time1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Series	3500
Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 1A Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 2ms Release Time 1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 1A Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 2ms Release Time 1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 2ms Release Time Ims Features Sealed - Hermetically Mounting Type Through Hole Termination Style	Coil Current	25mA
Contact Rating (Current) Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 2ms Release Time 1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 2ms Release Time 1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Ims Features Sealed - Hermetically Mounting Type Through Hole Termination Style 3.8 VDC 0.4 VDC 2ms Sems Embedded Through Hole PC Pin	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 2ms Release Time Ims Features Sealed - Hermetically Mounting Type Through Hole Termination Style O.4 VDC 2ms Ims Features PC Pin	Switching Voltage	500VAC, 500VDC - Max
Operate Time2msRelease Time1msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.8 VDC
Release Time 1ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.4 VDC
Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Operate Time	2ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	1ms
Termination Style PC Pin	Features	Sealed - Hermetically
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

3520-05-111 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3520-05-111 Payment Methods





















3520-05-111 Shipping Methods













If you have any question about 3520-05-111, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com