

352 Information



For Reference Only

Part Number 352

Manufacturer Adafruit Industries LLC

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 60W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









352 Specifications	5
--------------------	---

Manufacturer Part Number 352 Manufacturer Adafruit Industries LLC Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 110 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	552 Specifications	
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 110 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Manufacturer Part Number	352
Package - Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 110 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Manufacturer	Adafruit Industries LLC
Package - Series - Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 110 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input110 ~ 240 VACVoltage - Output12VCurrent - Output (Max)5APower (Watts)60WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input110 ~ 240 VACVoltage - Output12VCurrent - Output (Max)5APower (Watts)60WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 110 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Series	-
Input Type Voltage - Input 110 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension Cord 110 ~ 240 VAC 12V Current - Output Connex 240 VAC 12V Current - Output Connex 240 VAC 12V Current - Output Connex 240 VAC 12V 12V 12V 12V 12V 12V 12V 12	Region Utilized	North America
Voltage - Input 110 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 110 ~ 240 VAC 12V 12V 12V 12V 12V 12V 130 60W 140 150 150 160 170 170 170 170 170 170 17	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 12V 60W 60W 60W 7 60W 80 80 80 80 80 80 80 80 80	Input Type	Cord
Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Voltage - Input	110 ~ 240 VAC
Power (Watts) 60W No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Voltage - Output	12V
No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Current - Output (Max)	5A
Polarization Positive Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Power (Watts)	60W
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Polarization	Positive Center
Operating Temperature Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Efficiency	-
Size / Dimension 4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)	Operating Temperature	-
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.53" L x 1.97" W x 0.98" H (115.0mm x 50.0mm x 25.0mm)
		Report errors?

352 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

352 Payment Methods





















352 Shipping Methods













If you have any question about 352, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com