

3540-05-911 Information

Heisener.com

Part Number 3540-05-911 **Manufacturer** Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED SPST 500MA 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3540-05-911 Specifications

Manufacturer Part Number3540-05-911ManufacturerCoto TechnologyCategoryRelaysPackage-Series3500Relay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage500VAC, 500VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate TimeImsRelease Time0.2msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin		
Category Relays Signal Relays, Up to 2 Amps - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage SyDC Contact Form SpST-NO (1 Form A) Contact Rating (Current) Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 1ms Release Time 0.2ms Features Sealed - Hermetically Mounting Type Termination Style Reed Signal Relays, Up to 2 Amps Sed Southor 2 Amps Southor 2 Amps Southor 2 Amps Southor 3 Sub C Sub C	Manufacturer Part Number	3540-05-911
Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time Ims Release Time 0.2ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Coto Technology
Package-Series3500Relay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage500VAC, 500VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate TimeImsRelease Time0.2msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time Ims Release Time 0.2ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage500VAC, 500VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time1msRelease Time0.2msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage500VAC, 500VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time1msRelease Time0.2msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Series	3500
Coil Current 25mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Coil Current	25mA
Contact Rating (Current) Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Ims Release Time 0.2ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style 3.8 VDC 0.4 VDC One Time Ims Polyman Polyman	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time Ims Release Time 0.2ms Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	500VAC, 500VDC - Max
Operate Time1msRelease Time0.2msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.8 VDC
Release Time0.2msFeaturesSealed - HermeticallyMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	0.4 VDC
Features Sealed - Hermetically Mounting Type Through Hole Termination Style PC Pin	Operate Time	1ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	0.2ms
Termination Style PC Pin	Features	Sealed - Hermetically
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

3540-05-911 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3540-05-911 Payment Methods





















3540-05-911 Shipping Methods













If you have any question about 3540-05-911, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com