

3541-05-811 Information

Heisener.com

Part Number 3541-05-811 **Manufacturer** Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED DPST 500MA 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3541-05-811 Specifications

| Manufacturer Part Number 3541-05-811 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time Ims Release Time 0.2ms Features Sealed - Hermetically | | |
|---|--------------------------|-----------------------------|
| Category Relays Signal Relays, Up to 2 Amps Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time Ims Release Time 0.2ms | Manufacturer Part Number | 3541-05-811 |
| Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms | Manufacturer | Coto Technology |
| Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms | Category | Relays |
| Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms | | Signal Relays, Up to 2 Amps |
| Relay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage500VAC, 500VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate TimeImsRelease Time0.2ms | Package | - |
| Coil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage500VAC, 500VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time1msRelease Time0.2ms | Series | 3500 |
| Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms | Relay Type | Reed |
| Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms | Coil Type | Non Latching |
| Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms | Coil Current | 25mA |
| Contact Rating (Current) Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms | Coil Voltage | 5VDC |
| Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms | Contact Form | DPST (2 Form A) |
| Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 1ms Release Time 0.2ms | Contact Rating (Current) | 500mA |
| Turn Off Voltage (Min) Operate Time 1ms Release Time 0.2ms | Switching Voltage | 500VAC, 500VDC - Max |
| Operate Time 1ms Release Time 0.2ms | Turn On Voltage (Max) | 3.8 VDC |
| Release Time 0.2ms | Turn Off Voltage (Min) | 0.4 VDC |
| | Operate Time | 1ms |
| Features Sealed - Hermetically | Release Time | 0.2ms |
| | Features | Sealed - Hermetically |
| Mounting Type Through Hole | Mounting Type | Through Hole |
| Termination Style PC Pin | Termination Style | PC Pin |
| Report errors? | | Report errors? |

3541-05-811 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3541-05-811 Payment Methods




































If you have any question about 3541-05-811, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com