

3541-05-910 Information

Heisener.com

Part Number 3541-05-910 **Manufacturer** Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED DPST 500MA 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3541-05-910 Specifications

Manufacturer Part Number 3541-05-910 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time Ims Release Time 0.2ms		
Category Relays Signal Relays, Up to 2 Amps Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time Ims Release Time 0.2ms	Manufacturer Part Number	3541-05-910
Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms	Manufacturer	Coto Technology
Package - Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms	Category	Relays
Series 3500 Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage500VAC, 500VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate TimeImsRelease Time0.2ms	Package	-
Coil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage500VAC, 500VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time1msRelease Time0.2ms	Series	3500
Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms	Relay Type	Reed
Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms	Coil Current	25mA
Contact Rating (Current) Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms	Coil Voltage	5VDC
Switching Voltage 500VAC, 500VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 1ms Release Time 0.2ms	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 1ms Release Time 0.2ms	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 1ms Release Time 0.2ms	Switching Voltage	500VAC, 500VDC - Max
Operate Time 1ms Release Time 0.2ms	Turn On Voltage (Max)	3.8 VDC
Release Time 0.2ms	Turn Off Voltage (Min)	0.4 VDC
	Operate Time	1ms
	Release Time	0.2ms
Features Sealed - Hermetically	Features	Sealed - Hermetically
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

3541-05-910 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3541-05-910 Payment Methods


































If you have any question about 3541-05-910, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com