



355PMB700KBP0 Information



For Reference Only

Part Number 355PMB700KBP0
Manufacturer Illinois Capacitor
Category Capacitors
Film Capacitors

Description CAP FILM 3.5UF 700VDC CHAS MT

Package Rectangular Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









355PMB700KBP0 Specifications

Manufacturer Part Number 355PMB700KBP0 Manufacturer Illinois Capacitor Category Capacitors Package Rectangular Box Series PMB Capacitance 3.5µF Tolerance ±10% Voltage Rating - AC 420V Voltage Rating - DC 700V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 1.673" L x 1.299" W (42.50mm x 33.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features - Report errors?	*		
Category Capacitors Film Capacitors Package Rectangular Box Series PMB Capacitance 3.5µF Tolerance ±10% Voltage Rating - AC Voltage Rating - DC Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Size / Dimension 1.673" L x 1.299" W (42.50mm x 33.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features	Manufacturer Part Number	355PMB700KBP0	
Film CapacitorsPackageRectangular BoxSeriesPMBCapacitance3.5μFTolerance±10%Voltage Rating - AC420VVoltage Rating - DC700VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)2 mOhmOperating Temperature-40°C ~ 85°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension1.673" L x 1.299" W (42.50mm x 33.00mm)Height - Seated (Max)1.772" (45.00mm)Termination-Lead Spacing-ApplicationsDC Link, DC Filtering; High Frequency, Switching; SnubberFeatures-	Manufacturer	Illinois Capacitor	
Package Rectangular Box Series PMB Capacitance 3.5µF Tolerance ±10% Voltage Rating - AC 420V Voltage Rating - DC 700V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 1.673" L x 1.299" W (42.50mm x 33.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Category	Capacitors	
SeriesPMBCapacitance3.5μFTolerance±10%Voltage Rating - AC420VVoltage Rating - DC700VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)2 mOhmOperating Temperature-40°C ~ 85°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension1.673" L x 1.299" W (42.50mm x 33.00mm)Height - Seated (Max)1.772" (45.00mm)Termination-Lead Spacing-ApplicationsDC Link, DC Filtering; High Frequency, Switching; SnubberFeatures-		Film Capacitors	
Capacitance $3.5 \mu F$ Tolerance $\pm 10\%$ Voltage Rating - AC $420V$ Voltage Rating - DC $700V$ Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance) 2 mOhm Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension $1.673^{\circ}\text{L} \times 1.299^{\circ}\text{W} (42.50 \text{mm} \times 33.00 \text{mm})$ Height - Seated (Max) 1.772° (45.00 mm)Termination-Lead Spacing-ApplicationsDC Link, DC Filtering; High Frequency, Switching; SnubberFeatures-	Package	Rectangular Box	
Tolerance ±10% Voltage Rating - AC 420V Voltage Rating - DC 700V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 1.673" L x 1.299" W (42.50mm x 33.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Series	PMB	
Voltage Rating - AC Voltage Rating - DC 700V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 1.673" L x 1.299" W (42.50mm x 33.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Capacitance	3.5µF	
Voltage Rating - DC Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2 mOhm Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 1.673" L x 1.299" W (42.50mm x 33.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Tolerance	±10%	
Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 1.673" L x 1.299" W (42.50mm x 33.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Voltage Rating - AC	420V	
ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 1.673" L x 1.299" W (42.50mm x 33.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Voltage Rating - DC	700V	
Operating Temperature -40°C ~ 85°C Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 1.673" L x 1.299" W (42.50mm x 33.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Dielectric Material	Polypropylene (PP), Metallized	
Mounting Type Chassis Mount Package / Case Rectangular Box Size / Dimension 1.673" L x 1.299" W (42.50mm x 33.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	ESR (Equivalent Series Resistance)	2 mOhm	
Package / Case Rectangular Box Size / Dimension 1.673" L x 1.299" W (42.50mm x 33.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Operating Temperature	-40°C ~ 85°C	
Size / Dimension 1.673" L x 1.299" W (42.50mm x 33.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Mounting Type	Chassis Mount	
Height - Seated (Max) Termination Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Package / Case	Rectangular Box	
Termination - Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Size / Dimension	1.673" L x 1.299" W (42.50mm x 33.00mm)	
Lead Spacing - Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Height - Seated (Max)	1.772" (45.00mm)	
Applications DC Link, DC Filtering; High Frequency, Switching; Snubber Features -	Termination	-	
Features -	Lead Spacing	-	
	Applications	DC Link, DC Filtering; High Frequency, Switching; Snubber	
Report errors?	Features	-	
			Report errors?

355PMB700KBP0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

355PMB700KBP0 Payment Methods



















355PMB700KBP0 Shipping Methods













If you have any question about 355PMB700KBP0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com