

35CIK07 Information



For Reference Only

Part Number 35CIK07 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 35A 600VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









35CIK07 Specifications

Manufacturer Part Number35CIK07ManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesHRCI-MISCFuse TypeCartridgeCurrent Rating35AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.063" Dia x 2.283" L (27.00mm x 58.00mm)		
Category Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series HRCI-MISC Fuse Type Cartridge Current Rating 35A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Ceç, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Captridge Captridge Captridge Captridge Cylindrical, Blade Terminal (Bolt) Size / Dimension Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer Part Number	35CIK07
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series HRCI-MISC Fuse Type Cartridge Current Rating 35A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.283" L (27.00mm x 58.00mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesHRCI-MISCFuse TypeCartridgeCurrent Rating35AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.063" Dia x 2.283" L (27.00mm x 58.00mm)	Category	Circuit Protection
SeriesHRCI-MISCFuse TypeCartridgeCurrent Rating35AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.063" Dia x 2.283" L (27.00mm x 58.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 35A Voltage Rating - AC 600V Voltage Rating - DC	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Size / Dimen	Series	HRCI-MISC
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Fast Cet, CSA CE, CSA CURRATION CONTROL CONT	Current Rating	35A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Electrical, Industrial Features - CE, CSA OPERATION OF THE PROPERTY OF	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class - Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.283" L (27.00mm x 58.00mm)	Voltage Rating - DC	-
Features - Class - CSA Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.283" L (27.00mm x 58.00mm)	Response Time	Fast
Class - CE, CSA Operating Temperature - Streaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.283" L (27.00mm x 58.00mm)	Applications	Electrical, Industrial
Approvals CE, CSA Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.283" L (27.00mm x 58.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.283" L (27.00mm x 58.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.283" L (27.00mm x 58.00mm)	Approvals	CE, CSA
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.283" L (27.00mm x 58.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.283" L (27.00mm x 58.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.063" Dia x 2.283" L (27.00mm x 58.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.063" Dia x 2.283" L (27.00mm x 58.00mm)
		Report errors?

35CIK07 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

35CIK07 Payment Methods





















35CIK07 Shipping Methods













If you have any question about 35CIK07, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com