

3640AC124MAT3ASB

3640AC124MAT3ASB Information



For Reference Only

Part Number 3640AC124MAT3ASB Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.12UF 1KV X7R 3640

Package 3640 (9110 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3640AC124MAT3ASB Specifications

Category Capacitors Package 3640 (9110 Metric) Series - Capacitance 0.12µF Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing -		
Category Capacitors Package 3640 (9110 Metric) Series - Capacitance 0.12μF Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Manufacturer Part Number	3640AC124MAT3ASB
Package 3640 (9110 Metric) Series - Capacitance 0.12μF Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Manufacturer	AVX Corporation
Package 3640 (9110 Metric) Series - Capacitance 0.12µF Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 0.12μF Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.12µF Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Package	3640 (9110 Metric)
Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Capacitance	0.12μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style	Tolerance	±20%
Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Voltage - Rated	1000V (1kV)
Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Features	High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	3640 (9110 Metric)
Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Size / Dimension	0.360" L x 0.402" W (9.14mm x 10.20mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.100" (2.54mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

3640AC124MAT3ASB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3640AC124MAT3ASB Payment Methods



















3640AC124MAT3ASB Shipping Methods













If you have any question about 3640AC124MAT3ASB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com