

Heisener.com

3640Y2000565KXRWS2

3640Y2000565KXRWS2 Information

Part Number 3640Y2000565KXRWS2

Manufacturer Knowles Syfer Category Capacitors

Ceramic Capacitors

Description STACKICAP

Package 3640 (9110 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3640Y2000565KXRWS2 Specifications

•		
Category Capacitors Package 3640 (9110 Metric) Series StackiCap? Capacitance 5.6µF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style -	Manufacturer Part Number	3640Y2000565KXRWS2
Package 3640 (9110 Metric) Series StackiCap? Capacitance 5.6μF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 3640 (9110 Metric) Series StackiCap? Capacitance 5.6μF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style -	Category	Capacitors
Series StackiCap? Capacitance 5.6μF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 5.6μF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style -	Package	3640 (9110 Metric)
Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style - Surface Mount - S	Series	StackiCap?
Voltage - Rated Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style	Capacitance	5.6μF
Temperature Coefficient AYR Operating Temperature -55°C ~ 125°C Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesSoft Termination, Epoxy MountableRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface MountPackage / Case3640 (9110 Metric)Size / Dimension0.362" L x 0.417" W (9.20mm x 10.60mm)Height - Seated (Max)-Thickness (Max)0.177" (4.50mm)Lead Spacing-Lead Style-	Voltage - Rated	200V
Features Soft Termination, Epoxy Mountable Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R
Ratings - Boardflex Sensitive Failure Rate - Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style - Surface Mount	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style -	Features	Soft Termination, Epoxy Mountable
Failure Rate - Mounting Type Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case 3640 (9110 Metric) Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.362" L x 0.417" W (9.20mm x 10.60mm) Height - Seated (Max) - Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	3640 (9110 Metric)
Thickness (Max) 0.177" (4.50mm) Lead Spacing - Lead Style -	Size / Dimension	0.362" L x 0.417" W (9.20mm x 10.60mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.177" (4.50mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
Tepot enough		Report errors?

3640Y2000565KXRWS2 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3640Y2000565KXRWS2 Payment Methods





















3640Y2000565KXRWS2 Shipping Methods













If you have any question about 3640Y2000565KXRWS2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com