

3650-05-52

3650-05-52 Information

Heisener.com	 3650-05-52 Coto Technology Relays Signal Relays, Up to 2 Amps RELAY REED 3PST 250MA 5V - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



3650-05-52 Specifications

Manufacturer Part Number3650-05-52ManufacturerCoto TechnologyCategoryRelaysPackageSignal Relays, Up to 2 AmpsPackage-Series3600Relay TypeReedCoil TypeNon LatchingCoil Current14.28mACoil VoltageSVDCContact Form3PST (3 Form A)Contact Rating (Current)3LS VDCSwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time-Young TypeDe DirFurnier StateDe Dir		
CategoryRelaysCategorySignal Relays, Up to 2 AmpsPackage-Series3600Relay TypeReedCoil TypeNon LatchingCoil Current14.28mACoil VoltageSVDCContact Form3PST (3 Form A)Contact Rating (Current)500MASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Max)0.4 VDCOperate Time0.1msRelease Time-Mounting TypeTurough Hole	Manufacturer Part Number	3650-05-52
Number of the sector of the	Manufacturer	Coto Technology
Package-Series3600Relay TypeReedCoil TypeNon LatchingCoil Current14.28mACoil Voltage5VDCContact Form3PST (3 Form A)Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.1msFeatures-Mounting TypeThrough Hole	Category	Relays
Series3600Relay TypeReedCoil TypeNon LatchingCoil Current14.28mACoil Voltage5VDCContact Form3PST (3 Form A)Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.1msRelease Time0.1msFeatures-Mounting TypeThrough Hole		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current14.28mACoil VoltageSVDCContact Form3PST (3 Form A)Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)3.8 VDCOperate Time0.4 VDCRelease Time0.1msFeatures5.1msMounting TypeThrough Hole	Package	-
Coil TypeNon LatchingCoil Current14.28mACoil Voltage5VDCContact Form3PST (3 Form A)Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeatures-Mounting TypeThrough Hole	Series	3600
Coil Current14.28mACoil Voltage5VDCContact Form3PST (3 Form A)Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeatures-Mounting TypeThrough Hole	Relay Type	Reed
Coil Voltage5VDCContact Form3PST (3 Form A)Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeatures-Mounting TypeThrough Hole	Coil Type	Non Latching
Contact Form3PST (3 Form A)Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeatures-Mounting TypeThrough Hole	Coil Current	14.28mA
Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeatures-Mounting TypeThrough Hole	Coil Voltage	5VDC
Switching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeatures-Mounting TypeThrough Hole	Contact Form	3PST (3 Form A)
Turn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeatures-Mounting TypeThrough Hole	Contact Rating (Current)	250mA
Turn Off Voltage (Min)0.4 VDCOperate Time0.75msRelease Time0.1msFeatures-Mounting TypeThrough Hole	Switching Voltage	150VAC, 150VDC - Max
Operate Time0.75msRelease Time0.1msFeatures-Mounting TypeThrough Hole	Turn On Voltage (Max)	3.8 VDC
Release Time0.1msFeatures-Mounting TypeThrough Hole	Turn Off Voltage (Min)	0.4 VDC
Features-Mounting TypeThrough Hole	Operate Time	0.75ms
Mounting Type Through Hole	Release Time	0.1ms
	Features	-
Transford Stall	Mounting Type	Through Hole
PC PIn	Termination Style	PC Pin
Report error		Report errors?

3650-05-52 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 3650-05-52, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com