



36D152G100AD2A Information

Heisener.com

Part Number 36D152G100AD2A

Manufacturer Vishay Sprague

Category Capacitors

Aluminum Electrolytic Capacitors
on CAP ALUM 1500UF 100V SCREW

Description CAP ALUM 1500UF 100V SCREW **Package** Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









36D152G100AD2A Specifications

| Manufacturer Part Number 36D152G100AD2A Manufacturer Vishay Sprague Category Capacitors Package Radial, Can - Screw Terminals Scries 36D Capacitance 1500µF Tolerance -10%, +75% Voltage - Rated 100V ESR (Equivalent Series Resistance) - ESR (Equivalent Series Resistance) - Operating Temperature 40°C ~ 85°C Operating Temperature 90lar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.752" (120.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | • | |
|--|------------------------------------|----------------------------------|
| Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36D Capacitance 1500µF Tolerance -10%, +75% Voltage - Rated 100V ESR (Equivalent Series Resistance) -Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Manufacturer Part Number | 36D152G100AD2A |
| PackageRadial, Can - Screw TerminalsSeries36DCapacitance1500μFTolerance-10%, +75%Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.500" (12.70mm)Size / Dimension1.453" Dia (36.90mm)Height - Seated (Max)4.752" (120.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals | Manufacturer | Vishay Sprague |
| Package Radial, Can - Screw Terminals Series 36D Capacitance 1500µF Tolerance -10%, +75% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.752" (120.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Category | Capacitors |
| Series 36D Capacitance 1500μF Tolerance -10%, +75% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.752" (120.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | | Aluminum Electrolytic Capacitors |
| Capacitance 1500µF Tolerance -10%, +75% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.752" (120.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Package | Radial, Can - Screw Terminals |
| Tolerance -10%, +75% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.752" (120.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Raistance) - Lead Spacing Chassis Mount Radial, Can - Screw Terminals | Series | 36D |
| Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.500" (12.70mm)Size / Dimension1.453" Dia (36.90mm)Height - Seated (Max)4.752" (120.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals | Capacitance | 1500μF |
| ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing 5.2 / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Riood Hrs @ 85°C -000 Hrs @ 85°C -000 Hrs @ 85°C -001 - 40°C ~ 85° | Tolerance | -10%, +75% |
| Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency -Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 85°C -40°C ~ 85°C Following General Purpose - - - - - - - - - - - - - | Voltage - Rated | 100V |
| Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Rippedance Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.752" (120.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | ESR (Equivalent Series Resistance) | - |
| Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.752" (120.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Lifetime @ Temp. | 1000 Hrs @ 85°C |
| Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.752" (120.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Operating Temperature | -40°C ~ 85°C |
| Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.752" (120.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Polarization | Polar |
| Ripple Current - High Frequency Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.752" (120.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Applications | General Purpose |
| Impedance-Lead Spacing0.500" (12.70mm)Size / Dimension1.453" Dia (36.90mm)Height - Seated (Max)4.752" (120.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals | Ripple Current - Low Frequency | - |
| Lead Spacing0.500" (12.70mm)Size / Dimension1.453" Dia (36.90mm)Height - Seated (Max)4.752" (120.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals | Ripple Current - High Frequency | - |
| Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.752" (120.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Impedance | - |
| Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Lead Spacing | 0.500" (12.70mm) |
| Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Size / Dimension | 1.453" Dia (36.90mm) |
| Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Height - Seated (Max) | 4.752" (120.70mm) |
| Package / Case Radial, Can - Screw Terminals | Surface Mount Land Size | - |
| - | Mounting Type | Chassis Mount |
| Report errors? | Package / Case | Radial, Can - Screw Terminals |
| | | Report errors? |

36D152G100AD2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

36D152G100AD2A Payment Methods





















36D152G100AD2A Shipping Methods













If you have any question about 36D152G100AD2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com