



36D552F200DF2A Information

Heisener.com

Part Number 36D552F200DF2A
Manufacturer Vishay Sprague
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 5500UF 200V SCREW

Package Radial, Can - Screw Terminals
For the pricing/inventory/lead time, please contact

115

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









36D552F200DF2A Specifications

Manufacturer Part Number 36D552F200DF2A Manufacturer Vishay Sprague Category Capacitors Package Radial, Can - Screw Terminals Series 36D Capacitance 5500µF Tolerance -10%, +50% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	•	
Category Capacitors Package Radial, Can - Screw Terminals Series 36D Capacitance 5500µF Tolerance -10%, +50% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	36D552F200DF2A
PackageRadial, Can - Screw TerminalsSeries36DCapacitance5500μFTolerance-10%, +50%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.079" Dia (78.20mm)Height - Seated (Max)5.752" (146.10mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer	Vishay Sprague
Package Radial, Can - Screw Terminals Series 36D Capacitance 5500µF Tolerance -10%, +50% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series 36D Capacitance 5500μF Tolerance -10%, +50% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 5500μF Tolerance -10%, +50% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +50% Voltage - Rated 200V ESR (Equivalent Series Resistance) -1000 Hrs @ 85°C Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	36D
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.079" Dia (78.20mm)Height - Seated (Max)5.752" (146.10mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	5500μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Ri000 Hrs @ 85°C -000 Au°C ~ 85°C -010 Au°C ~	Tolerance	-10%, +50%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	200V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.079" Dia (78.20mm)Height - Seated (Max)5.752" (146.10mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	-
Lead Spacing1.252" (31.80mm)Size / Dimension3.079" Dia (78.20mm)Height - Seated (Max)5.752" (146.10mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.079" Dia (78.20mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	5.752" (146.10mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

36D552F200DF2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

36D552F200DF2A Payment Methods





















36D552F200DF2A Shipping Methods













If you have any question about 36D552F200DF2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com