



36DE173G075BC2A Information

Heisener.com

Part Number 36DE173G075BC2A

Manufacturer Vishay Sprague

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 17000UF 75V SCREW

PackageRadial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









36DE173G075BC2A Specifications

Manufacturer Part Number 36DE173G075BC2A Manufacturer Vishay Sprague Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36DE Capacitance 17000µF Tolerance 10%, +75% Voltage - Rated 75V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 95°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36DE Capacitance 17000µF Tolerance -10%, +75% Voltage - Rated 575V ESR (Equivalent Series Resistance) -Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 95°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.875" (22.22mm) Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	36DE173G075BC2A
Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36DE Capacitance 17000µF Tolerance -10%, +75% Voltage - Rated 75V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 95°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	Vishay Sprague
PackageRadial, Can - Screw TerminalsSeries36DECapacitance17000μFTolerance-10%, +75%Voltage - Rated75VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 95°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.875" (22.22mm)Size / Dimension2.079" Dia (52.80mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series 36DE Capacitance 17000µF Tolerance -10%, +75% Voltage - Rated 75V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 95°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 17000µF Tolerance -10%, +75% Voltage - Rated 75V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 95°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +75% Voltage - Rated 75V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 95°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Raistance) - Raid (Can - Screw Terminals	Series	36DE
Voltage - Rated75VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 95°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.875" (22.22mm)Size / Dimension2.079" Dia (52.80mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	17000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 95°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing 30.875" (22.22mm) Size / Dimension 4.252" (108.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	-10%, +75%
Lifetime @ Temp. Operating Temperature -40°C ~ 95°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 85°C -40°C ~ 95°C Following General Purpose - 0 General Purpose - 0 Ratial, Can - Screw Terminals	Voltage - Rated	75V
Operating Temperature -40°C ~ 95°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing 0.875" (22.22mm) Size / Dimension 4.252" (108.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Roll A0°C ~ 95°C Polar -40°C ~ 95°C -40°C ~ 95°C -40°C ~ 95°C	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 95°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.875" (22.22mm) Size / Dimension 2.079" Dia (52.80mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing0.875" (22.22mm)Size / Dimension2.079" Dia (52.80mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	-
Lead Spacing0.875" (22.22mm)Size / Dimension2.079" Dia (52.80mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 2.079" Dia (52.80mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case A.252" (108.00mm) - Chassis Mount Radial, Can - Screw Terminals	Lead Spacing	0.875" (22.22mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.079" Dia (52.80mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.252" (108.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

36DE173G075BC2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

36DE173G075BC2A Payment Methods





















36DE173G075BC2A Shipping Methods













If you have any question about 36DE173G075BC2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com