



36DX122F450DF2A Information

Heisener.com

Part Number 36DX122F450DF2A
Manufacturer Vishay Sprague
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1200UF 450V SCREW

PackageRadial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









36DX122F450DF2A Specifications

Manufacturer Part Number 36DX122F450DF2A Manufacturer Vishay Sprague Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36DX Capacitance 1200µF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36DX Capacitance 1200µF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	36DX122F450DF2A
PackageRadial, Can - Screw TerminalsSeries36DXCapacitance1200μFTolerance-10%, +50%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.079" Dia (78.20mm)Height - Seated (Max)5.752" (146.10mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer	Vishay Sprague
Package Radial, Can - Screw Terminals Series 36DX Capacitance 1200µF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series 36DX Capacitance 1200µF Tolerance -10%, ±50% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance1200μFTolerance-10%, +50%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.079" Dia (78.20mm)Height - Seated (Max)5.752" (146.10mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) -1000 Hrs @ 85°C Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	36DX
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Radial, Can - Screw Terminals	Capacitance	1200μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case RioOd Hrs @ 85°C -000 Hrs @ 85°C -0100 Hrs @ 8	Tolerance	-10%, +50%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case 1.000 Hrs @ 85°C -40°C ~ 85°C Folar General Purpose 1.252" (31.80mm) - Chassis Mount Radial, Can - Screw Terminals	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Rippedance Lead Spacing 1.252" (31.80mm) Size / Dimension Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	-
Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.079" Dia (78.20mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	5.752" (146.10mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
report errors.		Report errors?

36DX122F450DF2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

36DX122F450DF2A Payment Methods



















36DX122F450DF2A Shipping Methods













If you have any question about 36DX122F450DF2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com