



36DX124G040DJ2A Information

Heisener.com

Part Number 36DX124G040DJ2A
Manufacturer Vishay Sprague
Category Capacitors

Aluminum Electrolytic Capacitors

CAP ALUM 120000UF 40V SCREW

DescriptionCAP ALUM 120000UF 40V SCRPackageRadial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









36DX124G040DJ2A Specifications

Manufacturer Part Number 36DX124G040D12A Manufacturer Vishay Sprague Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36DX Capacitance 120000µF Tolerance -10%, +75% Voltage - Rated 40V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Package Radial, Can - Screw Terminals Series 36DX Capacitance 120000µF Tolerance -10%, +75% Voltage - Rated 40V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	36DX124G040DJ2A
Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36DX Capacitance 120000µF Tolerance -10%, +75% Voltage - Rated 40V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	Vishay Sprague
Package Radial, Can - Screw Terminals Series 36DX Capacitance 120000μF Tolerance -10%, +75% Voltage - Rated 40V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series 36DX Capacitance 120000µF Tolerance -10%, +75% Voltage - Rated 40V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 120000μF Tolerance -10%, +75% Voltage - Rated 40V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +75% Voltage - Rated 40V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Raistance) - Lead Spacing Chassis Mount Radial, Can - Screw Terminals	Series	36DX
Voltage - Rated40VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.079" Dia (78.20mm)Height - Seated (Max)8.752" (222.30mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	120000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	-10%, +75%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 85°C -40°C ~ 85°C -40°C ~ 85°C General Purpose - 1.252" (31.80mm) - 1.252" (31.80mm) 3.079" Dia (78.20mm) - Chassis Mount Radial, Can - Screw Terminals	Voltage - Rated	40V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Rippedance Lead Spacing 1.252" (31.80mm) Size / Dimension Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Ripple Current - High Frequency - Chassis Mount Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.079" Dia (78.20mm)Height - Seated (Max)8.752" (222.30mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	-
Lead Spacing1.252" (31.80mm)Size / Dimension3.079" Dia (78.20mm)Height - Seated (Max)8.752" (222.30mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.079" Dia (78.20mm) Height - Seated (Max) 8.752" (222.30mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.079" Dia (78.20mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	8.752" (222.30mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

36DX124G040DJ2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

36DX124G040DJ2A Payment Methods





















36DX124G040DJ2A Shipping Methods













If you have any question about 36DX124G040DJ2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com