



36DX132F450CF2A Information

Heisener.com

Part Number 36DX132F450CF2A
Manufacturer Vishay Sprague
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1300UF 450V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









36DX132F450CF2A Specifications

Manufacturer Part Number36DX132F450CF2AManufacturerVishay SpragueCategoryCapacitorsPackageRadial, Can - Screw TerminalsSeries36DXCapacitance1300µFTolerance-10%, +50%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.126° (28.60mm)Size / Dimension2.579° Dia (65.50mm)Height - Seated (Max)5.752° (146.10mm)Surface Mount Land Size-Mounting TypeChassis Mount		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 36DX Capacitance 1300µF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -	Manufacturer Part Number	36DX132F450CF2A
PackageRadial, Can - Screw TerminalsSeries36DXCapacitance1300µFTolerance-10%, +50%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.126" (28.60mm)Size / Dimension2.579" Dia (65.50mm)Height - Seated (Max)5.752" (146.10mm)Surface Mount Land Size-	Manufacturer	Vishay Sprague
PackageRadial, Can - Screw TerminalsSeries36DXCapacitance1300μFTolerance-10%, +50%Voltage - Rated450VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.126" (28.60mm)Size / Dimension2.579" Dia (65.50mm)Height - Seated (Max)5.752" (146.10mm)Surface Mount Land Size-	Category	Capacitors
Series 36DX Capacitance 1300µF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance 1300μF Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -	Package	Radial, Can - Screw Terminals
Tolerance -10%, +50% Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -	Series	36DX
Voltage - Rated 450V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -	Capacitance	1300μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) Surface Mount Land Size -	Tolerance	-10%, +50%
Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency Impedance Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.126" (28.60mm) Size / Dimension 4.579" Dia (65.50mm) Height - Seated (Max) Surface Mount Land Size General Purpose - Carrent - Hugh Frequency - 1.126" (28.60mm) 5.752" (146.10mm) - Surface Mount Land Size	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -	Applications	General Purpose
Impedance - Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -	Ripple Current - Low Frequency	-
Lead Spacing 1.126" (28.60mm) Size / Dimension 2.579" Dia (65.50mm) Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -	Ripple Current - High Frequency	-
Size / Dimension2.579" Dia (65.50mm)Height - Seated (Max)5.752" (146.10mm)Surface Mount Land Size-	Impedance	-
Height - Seated (Max) 5.752" (146.10mm) Surface Mount Land Size -	Lead Spacing	1.126" (28.60mm)
Surface Mount Land Size -	Size / Dimension	2.579" Dia (65.50mm)
	Height - Seated (Max)	5.752" (146.10mm)
Mounting Type Chassis Mount	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Package / Case Radial, Can - Screw Terminals	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

36DX132F450CF2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

36DX132F450CF2A Payment Methods



















36DX132F450CF2A Shipping Methods













If you have any question about 36DX132F450CF2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com