



### 36DX422G075AC2A Information

Heisener.com

Part Number 36DX422G075AC2A Manufacturer Vishay Sprague

**Category** Capacitors

Aluminum Electrolytic Capacitors

**Description**CAP ALUM 4200UF 75V SCREW**Package**Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 36DX422G075AC2A Specifications

Manufacturer Part Number         36DX422G075AC2A           Manufacturer         Vishay Sprague           Category         Capacitors           Package         Radial, Can - Screw Terminals           Scries         36DX           Capacitance         4200µF           Tolerance         -10%, +75%           Voltage - Rated         75V           ESR (Equivalent Scries Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Lead Spacing         0.500" (12.70mm)           Size / Dimension         1.453" Dia (36.90mm)           Height - Seated (Max)         4.252" (108.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	*	
Category         Capacitors           Package         Radial, Can - Screw Terminals           Series         36DX           Capacitance         4200µF           Tolerance         -10%, +75%           Voltage - Rated         75V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.500" (12.70mm)           Size / Dimension         1.453" Dia (36.90mm)           Height - Seated (Max)         4.252" (108.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer Part Number	36DX422G075AC2A
PackageRadial, Can - Screw TerminalsSeries36DXCapacitance4200μFTolerance-10%, +75%Voltage - Rated75VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.500" (12.70mm)Size / Dimension1.453" Dia (36.90mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer	Vishay Sprague
Package         Radial, Can - Screw Terminals           Series         36DX           Capacitance         4200µF           Tolerance         -10%, +75%           Voltage - Rated         75V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.500" (12.70mm)           Size / Dimension         1.453" Dia (36.90mm)           Height - Seated (Max)         4.252" (108.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Category	Capacitors
Series         36DX           Capacitance         4200μF           Tolerance         -10%, +75%           Voltage - Rated         75V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.500" (12.70mm)           Size / Dimension         1.453" Dia (36.90mm)           Height - Seated (Max)         4.252" (108.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance         4200μF           Tolerance         -10%, +75%           Voltage - Rated         75V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         1000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Lead Spacing         0.500" (12.70mm)           Size / Dimension         1.453" Dia (36.90mm)           Height - Seated (Max)         4.252" (108.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +75%  Voltage - Rated 75V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm)  Size / Dimension 1.453" Dia (36.90mm)  Height - Seated (Max) 4.252" (108.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Raistance) -  Ripple Current - Frequency - Chassis Mount  Radial, Can - Screw Terminals	Series	36DX
Voltage - Rated75VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.500" (12.70mm)Size / Dimension1.453" Dia (36.90mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	4200μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  1000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  -Ripple Current - High Frequency  Impedance  Lead Spacing  5.2 / Dimension  1.453" Dia (36.90mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Riood Hrs @ 85°C  -000 Hrs @ 85°C  -0100 Hrs @ 85	Tolerance	-10%, +75%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  O.500" (12.70mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  1000 Hrs @ 85°C  -40°C ~ 85°C  General Purpose  -  0.500"  1.453" Dia (36.90mm)  4.252" (108.00mm)  Chassis Mount  Radial, Can - Screw Terminals	Voltage - Rated	75V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Rippedance Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency -  Ripple Current - High Frequency -  Impedance -  Lead Spacing 0.500" (12.70mm)  Size / Dimension 1.453" Dia (36.90mm)  Height - Seated (Max) 4.252" (108.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications  General Purpose  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.500" (12.70mm) Size / Dimension 1.453" Dia (36.90mm) Height - Seated (Max) 4.252" (108.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing0.500" (12.70mm)Size / Dimension1.453" Dia (36.90mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	-
Lead Spacing0.500" (12.70mm)Size / Dimension1.453" Dia (36.90mm)Height - Seated (Max)4.252" (108.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 1.453" Dia (36.90mm)  Height - Seated (Max) 4.252" (108.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	0.500" (12.70mm)
Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Size / Dimension	1.453" Dia (36.90mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.252" (108.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

#### 36DX422G075AC2A Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 36DX422G075AC2A Payment Methods



















## 36DX422G075AC2A Shipping Methods













If you have any question about 36DX422G075AC2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com